

LED power supply CC for QUICK-FIXdc 15-50W 350-1400mA 25-54V non-dimmable NFC linear pre-programmed outputs 350/700/1050/1400mA

Order number: 5043

- SELV output protection for safety and flexibility in luminaires
- Very low current ripple, according to IEEE 1789 recommendation
- NFC technology for wireless programming
- Wide selection range for fixed current output
- Suitable for use in emergency lighting applications
- Active no-load protection
- Long life of up to 100,000 hours
- Ideal solution for Class I and Class II luminaires

Adjustable operating current: 350/700/1050/1400mA

Power consumption in watts: 15-50; protection class (IP): IP20; Input voltage: 186 - 240 AC/DC; Output current in A: ; Inrush current in A: 0; Tc temperature in °C: 80; Protection class: II; Overvoltage protection: 1000 V; Input voltage span: 198-264 AC / 186-280 DC; Warranty in years: 5; Input voltage range luminaire: 198-264 AC / 186-280 DC; ETIM Gruppen-ID: ECO02710; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: Yes; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; No dim function: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany
width: 30mm