

LED power supply CC for QUICK-FIXdc 2-50W 100-1400mA 20-54V DALI dimmable NFC linear adjustable current 350mA-1050mA by dip switch

Order number: 6074

- DALI-2 certified LED driver, 1-100% dimming range
- SELV output protection for safety and flexibility in luminaires
- Amplitude dimming for highest quality light output, according to IEEE 1789 recommendation
- NFC technology for wireless programming
- Suitable for use in emergency lighting applications
- Ideal solution for Class I and Class II

Settings selectable by dip switch: 350/400/500/600/700/800/900/1050mA

Power consumption in watts: 6-50; protection class (IP): IP20; Input voltage: 176 - 240 V AC/DC; Output current in A: ; Power Factor: 0,98; Inrush current in A: 0; Tc temperature in °C: 85; Protection class: II; Overvoltage protection: 1000 V; Output voltage: 20 - 54 DC; Input voltage span: 198-264; Warranty in years: 5; Input voltage range luminaire: 198-264; ETIM Group Identification Number: EC002710; Dimming DALI: Yes; No dim function: No; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany
width: 30mm