

LED power supply IP67 Proline 24 V/DC, 25A, 600W with MM mark

Order number: 3143-24

LED Power Supply IP67 High Quality 24 V/DC, 25A, 600 W

- **FEATURES:**
 - Universal input
 - overload protection by current limiting, auto recovery
 - protected against short circuit, overload, overvoltage
 - IP67, for indoor and outdoor applications
 - for LED and lighting applications
 - UL1310 Class 2
 - dimmable
 - EN61000-3-2, Class C, EN55015, EN61347-1, EN61347-2-13

- **TECHNICAL DATA:**
 - Input voltage range: 90...264V/AC (47...63Hz) 127...370V/ DC
 - Inrush current max: 65A
 - Overload protection: 95...1080 %.
 - Insulation voltage (I/P-O/P):
 - I/P-O/P: 3750V / AC
 - I/P-EF: 2000V / AC
 - O/P-FG: 500 V / AC
 - Operating temperature range: -30... 70°C
 - Weight: 1000 g

Inrush current in A: 0; Warranty in years: 7; ETIM Group Identification Number: EC002710; No dim function: No; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany
width: 144mm