

PRODUCT NO. 4235-050160-NOT

DOTLUX LED trunking system LINEAclick 25W 3W 5000K wide beam with emergency lighting module Made in Germany



to the product page

- Continued use of your existing mounting rail system
- Mounting without mechanical intervention in the mounting rail system with heat-resistant neodymium
 - magnetic brackets incl. safety rope
- Independent, integrated cable system with quick connectors
- Optimized transmittance of the patented LINEAclick lens from DOTLUX®
- Shadow-free light distribution thanks to innovative lens design
- Perfect cooling of the LED module thanks to aluminum core board
- LM80 certified LEDs with 40% current consumption
- Suitable for central battery (only DALI article no. 2814-350045 and 2813-450160)

WEIGHT IN KG	2.5	BEAM ANGLE	160
POWER CONSUMPTION IN WATTS	25+3	PROTECTION CLASS (IP)	IP40
NET LUMINOUS FLUX IN LUMENS	4250	INPUT VOLTAGE	176 - 240 V AC/DC
LUMEN PER WATT	168	Service life	
		COLOR TEMPERATURE IN KELVIN	5000
		COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,93
		INRUSH CURRENT IN A	0
		LUMEN PER WATT	168
		PROTECTION CLASS	I
		VOLTAGE TYPE	AC
		SWITCH CYCLES	> 200.000
		WARRANTY IN YEARS	7
		L80/B10	100000
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		LIFETIME L80/B10 AT 25°C	100000
		ETIM GRUPPEN-ID	EC002892
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
Dimensions			
length:	1530mm		
width:	73mm		
height:	61mm		

DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0