DOTLUX
LICHT IN BESTER QUALITÄT

PRODUCT NO. 5039

DOTLUX LED power supply ZIGBEE 3.0 3-38Watt 300-1050mA 10-54V dimmable

P out W	V out DC	I out DC
16	10...54	300 mA const.
18,5	10...54	350 mA const.
21,5	10...54	400 mA const.
24	10...54	450 mA const.
27	10...54	500 mA const.
29,5	10...54	550 mA const.
32	10...54	600 mA const.
35	10...54	650 mA const.
36	10...51	700 mA const.
38	10...50	750 mA const.
38	10...47	800 mA const.
38	10...44	850 mA const.
38	10...42	900 mA const.
38	10...40	950 mA const.
38	10...38	1 A const.
38	10...36	1,05 A const.

to the product page

- The flicker-free power supply is dimmable via ZIGBEE.
- With constant current technology (CC) it is suitable for constant current luminaires
- The connected constant current luminaires can be dimmed between 1%-100%
- The output current is adjustable:
    - 350/400/450/500/550/600/650/700/750/800/850/900/950/1000/1050mA
- To integrate with Philips Hue Bridge, start the search for new lights in the Hue app and turn on the driver only after the search has started
- MADE in EU

SUCCESSION ARTICLE	-
WEIGHT IN KG	0.148
POWER CONSUMPTION IN WATTS	3-38

Dimensions

length: 147mm
width: 44mm
height: 30mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 V AC
Output current in A	
POWER FACTOR	0,95
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	80
PROTECTION CLASS	II
OUTPUT VOLTAGE	10 - 54 DC
INPUT VOLTAGE SPAN	198-264 AC
INPUT VOLTAGE RANGE LUMINAIRE	198-264 AC
ETIM GRUPPEN-ID	EC002710
DIMMING ZIGBEE	Yes
DIMMING WITH PUSH-BUTTON	Yes
NO DIM FUNCTION	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany