

PRODUCT NO. 5043

**LED power supply CC for QUICK-FIXdc 15-50W 350-1400mA 25-54V non-dimmable NFC linear pre-programmed outputs 350/700/1050/1400mA**



to the product page

- SELV output protection for safety and flexibility in luminaires
- Very low current ripple, according to IEEE 1789 recommendation
- NFC technology for wireless programming
- Wide selection range for fixed current output
- Suitable for use in emergency lighting applications
- Active no-load protection
- Long life of up to 100,000 hours
- Ideal solution for Class I and Class II luminaires

Adjustable operating current: 350/700/1050/1400mA

<b>SUCCESSION ARTICLE</b>	-	<b>PROTECTION CLASS (IP)</b>	IP20
<b>PREDECESSOR ARTICLE</b>	4226	<b>INPUT VOLTAGE</b>	186 - 240 AC/DC
		Output current in A	
<b>WEIGHT IN KG</b>	0.198	<b>INRUSH CURRENT IN A</b>	0
<b>POWER CONSUMPTION IN WATTS</b>	15-50	<b>TC TEMPERATURE IN °C</b>	80
		<b>PROTECTION CLASS</b>	II
		<b>OVERVOLTAGE PROTECTION</b>	1000 V
		<b>INPUT VOLTAGE SPAN</b>	198-264 AC / 186-280 DC
		<b>WARRANTY IN YEARS</b>	5
		<b>INPUT VOLTAGE RANGE LUMINAIRE</b>	198-264 AC / 186-280 DC
<b>Dimensions</b>		<b>ETIM GRUPPEN-ID</b>	EC002710
<b>length:</b> 280mm		<b>DIMMING 0-10 V</b>	No
<b>width:</b> 30mm		<b>DIMMING 1-10 V</b>	No
<b>height:</b> 21mm		<b>DIMMING DALI</b>	Yes
		<b>DIMMING DMX</b>	No
		<b>DIMMING DSI</b>	No
		<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
		<b>DIMMING LINESWITCH</b>	No
		<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
		<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
		<b>DIMMING PHASE CUT-OFF</b>	No
		<b>DIMMING PROGRAMMABLE</b>	No
		<b>DIMMING RF</b>	No

<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>NO DIM FUNCTION</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN <math>\mu</math>S</b>	0
<b>BEG FUNDING</b>	Only relevant in Germany