

PRODUCT NO. 1938-455180

DOTLUX LED tube LUMENPLUS 150cm 22W 5500K frosted rotating end cap



to the product page



- **TECHNICAL ADVANTAGES**
 - Internal aluminum heat sink enables optimized thermal management
 - Polycarbonate cover with UV-protective coating (non-yellowing)
 - Future-oriented due to individually replaceable power supply units
 - Individually adjustable light beam angle due to patented end cap
 - Fail-safe, as each individual LED is controlled separately
- **FURTHER ADVANTAGES OF LUMENplus TUBES**
 - 5 years Dotlux warranty on driver and LEDs
 - Easy replacement of fluorescent tubes with starters
 - Immediately the full, optimal light output after switching on
 - LM80 certified LEDs
 - This tube is VDE certified
 - Version suitable for central battery on request

ENERGY

DOTLUX
1938-455180

A	▶	
B	▶	
C	▶	
D	▶	
E	▶	
F	▶	
G	▶	

22
kWh/1000h

2019/2015

SUCCESSION ARTICLE	-	BEAM ANGLE	180
PREDECESSOR ARTICLE	1938-355180 1938-155180 1938-1654-1	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.31	SERVICE LIFE	approx. 50.000 h at 25°C
POWER CONSUMPTION IN WATTS	22	COLOR TEMPERATURE IN KELVIN	5500
NET LUMINOUS FLUX IN LUMENS	3740	COLOR-RENDERING-INDEX	CRI > 83
LUMEN PER WATT	170	INRUSH CURRENT IN A	0
		LUMEN PER WATT	170
		HOUSING COLOUR	white
		SWITCH CYCLES	> 100.000
Dimensions		INPUT VOLTAGE SPAN	220-240 AC
length: 1500mm		WARRANTY IN YEARS	5
diameter: 26mm		INPUT VOLTAGE RANGE LUMINAIRE	220-240 AC
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	C
		ETIM GRUPPEN-ID	EC001959
		COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
		PULSE DURATION IN µS	0
		LIGHT COLOUR ACCORDING TO EN 12464-1	daylight white >5300 K
		BEG FUNDING COLOUR	Only relevant in Germany Multi-coloured