

PRODUCT NO. 3022-140120

**DOTLUX LED downlight CIRCLEflat 6W 4000K incl. driver**



to the product page

- Flat design with integrated power supply enables use even in difficult installation locations
- Backlight technology in robust design
- Sturdy mounting brackets ensure a secure hold

<b>SUCCESSION ARTICLE</b>	-
<b>PREDECESSOR ARTICLE</b>	3022-040120 2823 3022-0FW120
<b>WEIGHT IN KG</b>	0.066
<b>POWER CONSUMPTION IN WATTS</b>	6
<b>NET LUMINOUS FLUX IN LUMENS</b>	390
<b>LUMEN PER WATT</b>	65

**Dimensions**

**height:** 26mm  
**diameter:** 118mm

<b>BEAM ANGLE</b>	120
<b>PROTECTION CLASS (IP)</b>	IP20
<b>LIGHT COLOR</b>	white
<b>INPUT VOLTAGE</b>	220 - 240 V AC
<b>SERVICE LIFE</b>	approx. 30.000 h at 25°C
<b>COLOR TEMPERATURE IN KELVIN</b>	4000
<b>COLOR-RENDERING-INDEX</b>	CRI > 82
<b>POWER FACTOR</b>	0,6
<b>INRUSH CURRENT IN A</b>	0
<b>IK PROTECTION</b>	IK03
<b>LUMEN PER WATT</b>	65
<b>PROTECTION CLASS</b>	II
<b>VOLTAGE TYPE</b>	AC/DC
<b>HOUSING COLOUR</b>	white
<b>SUITED FOR EMERGENCY LIGHTING</b>	No
<b>SWITCH CYCLES</b>	> 60.000
<b>INSTALLATION OPENING WIDTH IN MM</b>	0
<b>INSTALLATION OPENING DIAMETER IN MM</b>	95-100
<b>INSTALLATION OPENING LENGHT IN MM</b>	0
<b>WARRANTY IN YEARS</b>	2
<b>L80/B10</b>	80000
<b>RATED CURRENT</b>	0.03
<b>SUITABLE FOR SURFACE MOUNTING</b>	Yes
<b>SUITABLE FOR MOUNTING</b>	Yes
<b>DIMMING WITHOUT DIMMER</b>	No

<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
<b>LIFETIME L80/B10 AT 25°C</b>	80000
<b>LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C</b>	30000
<b>ETIM GRUPPEN-ID</b>	EC001744
<b>WITH ILLUMINANT</b>	Yes
<b>SUITABLE FOR WALL MOUNTING</b>	No
<b>SUITABLE FOR SUSPENDED MOUNTING</b>	No
<b>SUITABLE FOR CEILING MOUNTING</b>	No
<b>SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1</b>	No
<b>LAMP HOLDER</b>	-
<b>MATERIAL COVER</b>	-
<b>TYPE OF CONTROL GEAR</b>	LED operating device current-controlled
<b>WITH CONTROL GEAR</b>	No
<b>DIMMING 0-10 V</b>	No
<b>DIMMING 1-10 V</b>	No
<b>DIMMING DALI</b>	No
<b>DIMMING DMX</b>	No
<b>DIMMING DSI</b>	No
<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>IMPACT STRENGTH</b>	IK03
<b>LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24</b>	No
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	No
<b>WITH MOVEMENT SENSOR</b>	No
<b>WITH LIGHT SENSOR</b>	No
<b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b>	No
<b>FILAMENT TEST ACCORDING TO IEC 60695-2-11</b>	650 °C - 30 s
<b>CONSTANT LIGHT OUTPUT (CLO)</b>	Yes
<b>PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471</b>	RG2
<b>OPERATION BY BLUETOOTH</b>	No
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No

<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>SUITABLE FOR LOW VOLTAGE CABLE SYSTEM</b>	No
<b>SUITABLE FOR CLAMP-MOUNTING</b>	Yes
<b>SUITABLE FOR LIGHT-TRACK MOUNTING</b>	No
<b>SUITABLE FOR PEDESTAL/FLOOR MOUNTING</b>	No
<b>SUITABLE FOR TRAVERSE MOUNTING</b>	No
<b>EXCHANGEABLE CONTROL GEAR</b>	No
<b>SUITABLE FOR LAMP POWER IN W</b>	5,8
<b>LAMP TYPE</b>	LED not exchangeable
<b>EMERGENCY POWER SUPPLY INTEGRATED</b>	No
<b>SURFACE BRUSHED</b>	No
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	30000
<b>LIFETIME L90/B10 AT 25°C</b>	7500
<b>PULSE DURATION IN µS</b>	0
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	G
<b>LIGHT SHARING</b>	Asymmetric
<b>LIGHT OUTLET</b>	Direct
<b>TYPE OF WIRING</b>	Suitable for through wiring
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>LUMINOUS FLUX ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>SURFACE PROTECTION</b>	Plastic-coated
<b>ADJUSTABILITY</b>	Not adjustable
<b>LIGHT DISTRIBUTOR</b>	Other
<b>REFLECTOR</b>	None
<b>BEAM ANGLE</b>	Extreme wide beam >80°
<b>DEGREE OF PROTECTION (NEMA)</b>	Other
<b>CONNECTION TYPE</b>	Other