

PRODUCT NO. 5109

Light management system Controller plus Bluetooth DT8 (without connection cable)





to the product page



- HCL control unit for controlling luminaires with HCL colored light control based on DALI.
- Automatic control of color temperature and brightness via freely programmable light curve
- Automatic switch-on and switch-off times of the light
- Simulation of the course of the sun during the day
- Programming via Lumobi App
- Works only in combination with clock module (art. no. 5110) or touch panel (art. no. 5111)
- Optionally a motion and brightness sensor (art. no. 5112) can be integrated

- For up to 32 luminaires

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
PREDECESSOR ARTICLE	4182	INPUT VOLTAGE	176 - 240 V AC/DC
		SERVICE LIFE	approx. 50.000h at 70°C
WEIGHT IN KG	0.09	INRUSH CURRENT IN A	0
		TC TEMPERATURE IN °C	70
		SWITCH CYCLES	> 100.000
		ETIM GRUPPEN-ID	EC002710
Dimensions		NO DIM FUNCTION	No
		COMPATIBLE WITH CASAMBI	No
length: 130mm		COMPATIBLE WITH APPLE HOMEKIT	No
width: 30mm		COMPATIBLE WITH GOOGLE ASSISTANT	No
height: 21mm		COMPATIBLE WITH AMAZON ALEXA	No
		PULSE DURATION IN μ S	0
		BEG FUNDING	Only relevant in Germany