

PRODUCT NO. 5116

## CASAMBI DALI interface/gateway passive



to the product page



### CASAMBI to DALI gateway

Ideal for DALI group control (max. 64DALI devices with DALI power supply Art.5119)

- Up to 250 DALI devices per interface depending on the DALI power supply (max. 250mA=249 devices)
- Through-wirable DALI interface for convenient control of DALI light sources via Casambi app
- Suitable for integrating a conventional DALI sensor into the CASAMBI world
- passive device, external power supply via DALI cable required! Compatible with DALI power supply (item no. 5119)
- compatible with sensor (art. no. 5117), radio remote control (art. no. 5120) and wall switch (art. no. 5121)
- Various pre-installed profiles can be selected in the CASAMBI app
- Control of DALI components via CASAMBI
- Control of CASAMBI components via DALI
- DALI individual addressing or DALI group control/broadcast
- Complete control via CASAMBI app:
  - Control of brightness and light color
  - Configuration of luminaires and luminaire networks
  - Creating scenes and animations (color gradients)
  - Intelligent timer and gallery functions

<b>SUCCESSION ARTICLE</b>	-	<b>PROTECTION CLASS (IP)</b>	IP20
<b>WEIGHT IN KG</b>	0.02	<b>INPUT VOLTAGE SPAN</b>	9,5-22,5 DC
		<b>INPUT VOLTAGE RANGE LUMINAIRE</b>	9,5-22,5 DC
		<b>ETIM GRUPPEN-ID</b>	EC002924
		<b>BEG FUNDING</b>	Only relevant in Germany

### Dimensions

**length:** 40mm

**width:** 36mm

**height:** 14mm