

PRODUCT NO. 5117

CASAMBI PIR motion and brightness sensor



to the product page

- PIR motion and brightness sensor for convenient operation of luminaires via CASAMBI app
- including bezels to optimize the sensor detection range
- sturdy mounting brackets ensure a secure hold
- mounting height: max. 4m (ceiling mounting)
- detection area: max. 10x4m (ceiling mounting)
- compatible with surface mount housing (art. no. 5118)
- power supply via mains
- complete control via CASAMBI App:
- presence/absence detection
- ambient light dependent control of luminaires/scenes
- Light duration and fade-in/fade-out times

Different functions of the sensor possible:

1. on/off function on pre-installed scene via sensor, then 0% luminosity with optional fade-out time.
2. on/off function on pre-installed scene via sensor with adjustable afterglow duration/force with optional fade-in/fade-out time
3. deactivation of manual control and exclusive control via sensor

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.092	INPUT VOLTAGE	220 - 240 V AC
		CONTROL METHOD	other
		ETIM GRUPPEN-ID	EC002924
		SUITABLE FOR CASAMBI	Yes
		BEG FUNDING	Only relevant in Germany

Dimensions

length: 56mm

diameter: 85mm