

PRODUCT NO. 2528-130120

DOTLUX LED panel TOPround Ø225mm 18W 3000K with mounting frame round



to the product page

- Clear, linear design
- Integrated power supply
- Good color rendering (Ra > 82)

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	2528-1FW120 2528-0FW120 2528-030120
WEIGHT IN KG	0.26
POWER CONSUMPTION IN WATTS	18
NET LUMINOUS FLUX IN LUMENS	1620
LUMEN PER WATT	90

Dimensions

diameter: 225mm
height: 35mm

BEAM ANGLE	120
PROTECTION CLASS (IP)	IP20
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 20.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,5
INRUSH CURRENT IN A	0
IK PROTECTION	IK03
LUMEN PER WATT	90
PROTECTION CLASS	II
VOLTAGE TYPE	AC
HOUSING COLOUR	white
SUITED FOR EMERGENCY LIGHTING	No
SWITCH CYCLES	> 40.000
WARRANTY IN YEARS	2
L80/B10	29500
RATED CURRENT	0.1
SUITABLE FOR SURFACE MOUNTING	Yes
SUITABLE FOR MOUNTING	No
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	29500
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	59000

ETIM GRUPPEN-ID	EC002892
WITH ILLUMINANT	No
SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	Yes
SUITABLE FOR LIGHT LINE CONFIGURATION	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	No
LAMP HOLDER	-
MATERIAL COVER	-
TYPE OF CONTROL GEAR	LED operating device current-controlled
WITH CONTROL GEAR	No
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK03
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	650 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	Yes
TYPE OF WIRING	Through wiring included
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG2
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No

IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	No
SUITABLE FOR LAMP POWER IN W	17.7
LAMP TYPE	LED not exchangeable
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	59000
LIFETIME L90/B10 AT 25°C	14750
PULSE DURATION IN µS	0
LIFETIME L90/B50 AT 25°C	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	-
LIGHT SHARING	Asymmetric
LIGHT OUTLET	Direct
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
SURFACE PROTECTION HOUSING	Plastic-coated
TYPE OF GRID	None
LIGHT DISTRIBUTOR	Other
BEAM ANGLE	Extreme wide beam >80°
DEGREE OF PROTECTION (NEMA)	Other
CONNECTION TYPE	Other