

PRODUCT NO. 5136

LED power supply CC for QUICK-FIXdc 5-25W 150-500mA 25-54V non-dimmable NFC linear pre-programmed outputs 150/250/350/500mA



to the product page

- SELV output protection for safety and flexibility in luminaires
- Very low current ripple, according to IEEE 1789 recommendation
- NFC technology for wireless programming
- Wide selection range for fixed current output
- Suitable for use in emergency lighting applications
- Active no-load protection
- Long life of up to 100,000 hours
- Ideal solution for Class I and Class II luminaires

Selectable operating current: 150/250/350/500mA

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.19	INRUSH CURRENT IN A	0
POWER CONSUMPTION IN WATTS	5-25	TC TEMPERATURE IN °C	80
		PROTECTION CLASS	II
		OVERVOLTAGE PROTECTION	1000 V
		OUTPUT VOLTAGE	25 - 54 DC
		INPUT VOLTAGE SPAN	198-264 AC / 176-280 DC
		WARRANTY IN YEARS	5
		INPUT VOLTAGE RANGE LUMINAIRE	198-264 AC / 176-280 DC
		ETIM GRUPPEN-ID	ECC02710
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No
		DIMMING RF	No
		DIMMING SINE WAVE REDUCTION	No

Dimensions

length: 280mm
width: 30mm
height: 21mm

DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany