

PRODUCT NO. 3140-1

LED power supply CC 9-15W 200-350mA 16W 26-42V dimmable phase section













to the product page



- The power supply is dimmable via phase cut dimmer
- With constant current technology (CC) it is suitable for constant current luminaires
- The connected constant current luminaires can be dimmed between 10%-100%
- Suitable dimmers: JUNG 1224 LED UDE, Eltako EUD61NPL-230V, GIRA Mini2440 00 and many more
- The output current is adjustable: 200/250/300/350mA
- The power supply is set to 200mA by default

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	3140

WEIGHT IN KG	0.079
POWER CONSUMPTION IN WATTS	9-15

Dimensions

length: 122mm width: 41mm height: 23mm
 PROTECTION CLASS (IP)
 IP20

 INPUT VOLTAGE
 220 - 240 V AC

 OUTPUT CURRENT IN A
 0,2-0,35

POWER FACTOR 0,98
INRUSH CURRENT IN A 0
TC TEMPERATURE IN °C 85
PROTECTION CLASS II
OVERVOLTAGE PROTECTION 1000 V
OUTPUT VOLTAGE 26 - 42 DC
INPUT VOLTAGE SPAN 180-264 AC

WARRANTY IN YEARS 5

INPUT VOLTAGE RANGE LUMINAIRE180-264 ACETIM GRUPPEN-IDEC002710

DIMMING MAINS VOLTAGE

MODULATION

 DIMMING PHASE CUT-OFF
 Yes

 NO DIM FUNCTION
 No

 COMPATIBLE WITH CASAMBI
 No

 COMPATIBLE WITH APPLE HOMEKIT
 No

 COMPATIBLE WITH GOOGLE ASSISTANT
 No

COMPATIBLE WITH AMAZON ALEXA

DIMMING PHASE CUT-ON Yes **PULSE DURATION IN µS** 0

BEG FUNDING Only relevant in Germany

Yes

No