


PRODUCT NO. 3138-1

LED power supply CC 13-30W 500-700mA 26-42V dimmable phase-down/phase-up



to the product page

- The power supply is dimmable via phase cut dimmer or phase angle dimmer
- With the constant current technology (CC) it is suitable for luminaires with constant current
- The connected constant current luminaires can be dimmed between 10%-100%
- Suitable dimmers: JUNG 1224 LED UDE, Eltako EUD61NPL-230V, GIRA Mini2440 00, and many more.
- The output current is adjustable: 500/550/600/700mA
- The power supply is set to 500mA by default

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
PREDECESSOR ARTICLE	3138 3139	INPUT VOLTAGE	220 - 240 V AC
WEIGHT IN KG	0.139	OUTPUT CURRENT IN A	0,5-0,7
POWER CONSUMPTION IN WATTS	13-30	INRUSH CURRENT IN A	0
		TC TEMPERATURE IN °C	85
		PROTECTION CLASS	II
		OVERVOLTAGE PROTECTION	1000 V
		OUTPUT VOLTAGE	26 - 42 DC
Dimensions		INPUT VOLTAGE SPAN	198-264 AC
length: 138mm		WARRANTY IN YEARS	5
width: 44mm		INPUT VOLTAGE RANGE LUMINAIRE	198-264 AC
height: 30mm		ETIM GRUPPEN-ID	EC002710
		DIMMING MAINS VOLTAGE MODULATION	Yes
		DIMMING PHASE CUT-OFF	Yes
		NO DIM FUNCTION	No
		DIMMING PHASE CUT-ON	Yes
		PULSE DURATION IN µS	0
		BEG FUNDING	Only relevant in Germany