

PRODUCT NO. 4258-1

LED power supply CC 27-40W 700-1050mA 27-38V dimmable phase-on/phase-off















- The power supply is dimmable via phase cut dimmer or phase angle dimmer
- With constant current technology (CC) it is suitable for constant current luminaires
- The connected constant current luminaires can be dimmed between 10%-100%
- Suitable dimmers: JUNG 1224 LED UDE, Eltako EUD61NPL-230V, GIRA Mini2440 00 and many
- The output current is adjustable: 700/800/950/1050mA
- The power supply is set to 700mA by default

SUCCESSION ARTICLE PREDECESSOR ARTICLE 4258

WEIGHT IN KG 0.15 **POWER CONSUMPTION IN WATTS** 27-40

Dimensions

length: 173mm width: 44mm height: 30mm

PROTECTION CLASS (IP) IP20

INPUT VOLTAGE 220 - 240 V AC

OUTPUT CURRENT IN A 0,7-1,05 **POWER FACTOR** 0.97 **INRUSH CURRENT IN A** Π TC TEMPERATURE IN °C 85 PROTECTION CLASS **OVERVOLTAGE PROTECTION** 1000 V **OUTPUT VOLTAGE** 27 - 38 DC INPUT VOLTAGE SPAN 198-264 AC

WARRANTY IN YEARS

INPUT VOLTAGE RANGE LUMINAIRE 198-264 AC ETIM GRUPPEN-ID EC002710

DIMMING MAINS VOLTAGE

Yes **MODULATION**

DIMMING PHASE CUT-OFF Yes NO DIM FUNCTION No **COMPATIBLE WITH CASAMBI** Nο **COMPATIBLE WITH APPLE HOMEKIT** No **COMPATIBLE WITH GOOGLE** No

COMPATIBLE WITH AMAZON ALEXA

No **DIMMING PHASE CUT-ON** Yes PULSE DURATION IN µS

BEG FUNDING Only relevant in Germany

ASSISTANT