

PRODUCT NO. 5169-060160

**DOTLUX LED module ACplus 1.5W 160° IP67 6000K 100 chain**



to the product page



- LED module for direct connection to 230V, without additional power supply unit
- 160° special lens enables homogeneous illumination even with shallow installation depths
- Quick installation due to 20m chain with 100 modules, can be shortened individually
- Parallel connection of several chains is possible for larger areas. (Series connection of several chains not possible)
- Yellowing-proof housing ensures stable light output
- Easy mounting of the individual modules by screw hole or carrierless adhesive tape on the backside
- We recommend the use of the overvoltage protection Art.5044

**ENERGY**

**DOTLUX**  
5169-060160

**1**  
kWh/1000h

<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	160
<b>WEIGHT IN KG</b>	1.22	<b>PROTECTION CLASS (IP)</b>	IP67
<b>POWER CONSUMPTION IN WATTS</b>	1.5	<b>LIGHT COLOR</b>	white
<b>NET LUMINOUS FLUX IN LUMENS</b>	150	<b>INPUT VOLTAGE</b>	220 - 240 V AC
<b>LUMEN PER WATT</b>	100	<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
		<b>COLOR TEMPERATURE IN KELVIN</b>	6000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>POWER FACTOR</b>	0,94
		<b>AMOUNT OF LED/M</b>	5
		<b>TC TEMPERATURE IN °C</b>	60
		<b>LUMEN PER WATT</b>	100
		<b>LIGHT FLUX LM/M</b>	750
		<b>PROTECTION CLASS</b>	II
		<b>VOLTAGE TYPE</b>	AC
		<b>SELF-STICKING</b>	yes
		<b>SWITCH CYCLES</b>	> 100.000
		<b>INPUT VOLTAGE SPAN</b>	220-240 AC
		<b>WARRANTY IN YEARS</b>	3
		<b>L80/B10</b>	25000
		<b>DIMMING WITHOUT DIMMER</b>	No
		<b>INPUT VOLTAGE RANGE LUMINAIRE</b>	220-240 AC
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	E
		<b>LIFETIME L80/B10 AT 25°C</b>	25000
		<b>LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C</b>	50000
		<b>ETIM GRUPPEN-ID</b>	EC002706

**Dimensions**

**length:** 20000mm  
**width:** 20mm  
**height:** 11mm

<b>DEGREE OF PROTECTION (NEMA)</b>	1
<b>CONSTANT LIGHT OUTPUT (CLO)</b>	Yes
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>EXCHANGEABLE CONTROL GEAR</b>	No
<b>SUITABLE FOR DIMMER</b>	No
<b>LAMP TYPE</b>	LED not exchangeable
<b>WITH CONNECTION SET</b>	No
<b>WITH END PIECE</b>	No
<b>WITH PROTECTIVE COVER</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	50000
<b>LIFETIME L90/B10 AT 25°C</b>	12500
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	-
<b>TYPE OF WIRING</b>	Suitable for through wiring
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>MOUNTING METHOD</b>	Other
<b>TYPE OF CONTROL GEAR</b>	Not required
<b>CONNECTION TYPE</b>	Solder