

PRODUCT NO. 5199-040110

DOTLUX LED panel FLATtwice 1200x300mm 40W UGR<19 4000K DALI dimmable



to the product page

- Ultra flat pendant luminaire with sturdy, elegant profile housing
- Stylish appearance thanks to screwless design and elegant Y-rope suspension
- Quick installation thanks to magnetic ceiling box
- Direct and indirect light distribution in the ratio 70% DOWN / 30% UP
- Glare-free, homogeneous and shadow-free light distribution / smooth top UGR<19

SUCCESSION ARTICLE	-	BEAM ANGLE	110
WEIGHT IN KG	4.198	PROTECTION CLASS (IP)	IP20
POWER CONSUMPTION IN WATTS	40	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	4200	INPUT VOLTAGE	220 - 240 V AC
LUMEN PER WATT	105	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	4000
		COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,9
Dimensions		INRUSH CURRENT IN A	0
length: 1200mm		LUMEN PER WATT	105
width: 300mm		PROTECTION CLASS	I
		HOUSING COLOUR	white
		GLARE-FREE	UGR < 19
		SWITCH CYCLES	> 100.000
		SIMILAR TO RAL-COLOUR	9003
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GROUP IDENTIFICATION NUMBER	ECC002892
		MATERIAL COVER	Plastic matt/satinized
		DIMMING WITH PUSH-BUTTON	Yes
		NO DIM FUNCTION	No
		COLOR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
		COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
		COMPATIBLE WITH CASAMBI	No

COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
DIMMING DALI-2	Yes
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	E
COLOUR OF LIGHT ADJUSTABLE	No