

PRODUCT NO. 5098

DOTLUX LED safety light EXITtop with self-test incl. 2 interchangeable lenses white 8h



to the product page

- Replaceable battery with a lighting duration of 8 hours
- Integrated control LED for operating status
- Only suitable for stand-by mode. If the light is supplied with mains power, the integrated rechargeable battery is charging and the light is in stand-by mode.
- Incl. two easy to change lenses
 - Corridor lighting (asymmetric)
 - wide beam
- Automatic self-test function

SUCCESSION ARTICLE	-	BEAM ANGLE	180
WEIGHT IN KG	0.481	PROTECTION CLASS (IP)	IP20
POWER CONSUMPTION IN WATTS	0,7	INPUT VOLTAGE	220 - 240 V AC
NET LUMINOUS FLUX IN LUMENS	240	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	5000
		POWER FACTOR	0,3
		BATTERY RUNTIME	8h
		PROTECTION CLASS	II
Dimensions		HOUSING COLOUR	black
height: 62mm		INSTALLATION OPENING DIAMETER IN MM	110-120
diameter: 140mm		INPUT VOLTAGE SPAN	220-240 AC
		WARRANTY IN YEARS	3
		INPUT VOLTAGE RANGE LUMINAIRE	220-240 AC
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC001957
		BEG FUNDING	Only relevant in Germany
		ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHE	-
		MATERIAL COVER	Other