

PRODUCT NO. 5250

**LED-Netzteil CC 5-19W 100-380mA 5-50V dimmbar DALI inkl DC 5,5mm Anschlusskabel**



to the product page

**WEIGHT IN KG** 0.008  
**POWER CONSUMPTION IN WATTS** 3-19  
**LUMINAIRES PER CIRCUIT BREAKER** B16=50

**Dimensions**

**length:** 108mm  
**width:** 52mm  
**height:** 22mm

**PROTECTION CLASS (IP)** IP20  
**INPUT VOLTAGE** 220 - 240 V AC  
**FREQUENCY RANGE IN HZ** 50/60  
Output current in A  
**POWER FACTOR** 0,96  
**PROTECTION CLASS** II  
**VOLTAGE TYPE** AC/DC  
**SUITED FOR EMERGENCY LIGHTING** yes  
**OVERVOLTAGE PROTECTION** 1000 V  
**CORD LENGTH IN M** 0.15  
**OUTPUT VOLTAGE** 3 - 50 DC  
**INPUT VOLTAGE SPAN** 110-240 AC / 176-276 DC  
**WARRANTY IN YEARS** 2  
**INPUT VOLTAGE RANGE LUMINAIRE** 110-240 AC / 176-276 DC  
**ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015** not required  
**DIMMING DALI** Yes  
**SUITABLE FOR EMERGENCY LIGHTING** Yes  
**DIMMING DALI-2** Yes