

PRODUCT NO. 1809-1FW120-B-Ware

DOTLUX LED-Panel FLATugr 1195x295mm 40W UGR<19 COLORselect B-Ware



to the product page

- Weißer Rahmen und Anschlusskabel mit Steckverbinder
- UGR < 19 für Bildschirmarbeitsplätze geeignet
- 3-Step MacAdam Binning - Konstante Farbtemperatur aller Leuchten
- Hohe Anzahl an niedrig bestromten LEDs garantieren eine lange Lebensdauer der LED und in der Folge geringe Wartungskosten!

SUCCESSION ARTICLE	1809-2FW090	BEAM ANGLE	120
PREDECESSOR ARTICLE	1809-0FW120	PROTECTION CLASS (IP)	IP40
WEIGHT IN KG	2.5	LIGHT COLOR	multicoloured
POWER CONSUMPTION IN WATTS	40	SERVICE LIFE	approx. 50.000 h at 25°C
NET LUMINOUS FLUX IN LUMENS	max. 3900	COLOR TEMPERATURE IN KELVIN	3000/4000/5700
LUMEN PER WATT	107	COLOR-RENDERING-INDEX	CRI > 92
		POWER FACTOR	0,9
		LUMEN PER WATT	107
		PROTECTION CLASS	II
Dimensions		GLARE-FREE	UGR < 19
		SWITCH CYCLES	> 100.000
		WARRANTY IN YEARS	0
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC002892
		DIMMING DEPENDING ON CONTROL GEAR	Yes