

PRODUCT NO. 5275

DOTLUX DMX receiver/dimmer with integrated stand alone function 4 channels 12-24V DC 4x5A



to the product page



- Digital numerical display, DMX start address setting via buttons.
- Flexible input voltage 12-24V with screw terminal.
- RDM function can realize communication between DMX master and decoder.
- DMX preset for 1/2 or 4color stripes.
- More suitable for video recording by adjustable PWM frequency 2000/500Hz
- More beautiful dimming effects by adjustable dimming curve (Logarithmic or Linear)
- Stand-alone mode for RGB/RGBW and 4-channel dimmer. Built-in programs instead of DMX signal
- Suitable for single color, dual color, RGB or RGBW constant voltage LED strips or modules
- Built-in protection circuit (overload, overheat, short circuit)

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.112	OUTPUT VOLTAGE	12 - 24 DC
		WARRANTY IN YEARS	3
		CONTROL METHOD	DMX
		ETIM GRUPPEN-ID	EC002924
Dimensions		COMPATIBLE WITH CASAMBI	No
		COMPATIBLE WITH APPLE HOMEKIT	Yes
		COMPATIBLE WITH GOOGLE ASSISTANT	No
width: 50mm		COMPATIBLE WITH AMAZON ALEXA	No
height: 23mm		BEG FUNDING	Only relevant in Germany
length: 170mm			