

PRODUCT NO. 5321-099140

DOTLUX Mirror light TRENDOsocket 10W 3000/4000/5700K COLORselect







to the product page

- Modern, stylish design with integrated Schuko socket outlet and side switch
- Maximum lighting surface without visible screw connections
- EASYbase platform enables quick and easy installation
- Installation on existing drill holes possible thanks to free surface on the base plate
- 2 cable inlets pre-installed (individual inlets can be drilled into the aluminum base if required)
- Simply set your desired light color yourself, one article number three light colors through COLORselect
- Sustainable product design thanks to easily replaceable components

			440
			140
WEIGHT IN KG	0.73	PROTECTION CLASS (IP)	IP44
POWER CONSUMPTION IN WATTS	10	LIGHT COLOR	multicoloured
NET LUMINOUS FLUX IN LUMENS	1050	INPUT VOLTAGE	220 - 240 V AC
LUMEN PER WATT	105	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000/4000/5700
		COLOR-RENDERING-INDEX	CRI > 82
		INRUSH CURRENT IN A	0
Dimensions		IK PROTECTION	IKO8
		LUMEN PER WATT	105
length: 599mm		PROTECTION CLASS	I
width: 85mm		HOUSING COLOUR	multicoloured
height: 57mm		SWITCH CYCLES	> 100.000
		INPUT VOLTAGE SPAN	220-240 AC
		WARRANTY IN YEARS	5
		SIMILAR TO RAL-COLOUR	9006
		INPUT VOLTAGE RANGE LUMINAIRE	220-240 AC
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC002892
		MATERIAL COVER	Plastic matt/satinized
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No



DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK08
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
COLOUR OF LIGHT ADJUSTABLE	Positions
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	E