

PRODUCT NO. 5334

DOTLUX LED power supply CC 600mA-1050mA 24-42W 220-240V



to the product page

- LED Power Supply for LED Panels 950mA
- With constant current (CC) technology, it is suitable for constant current luminaires
- The output current is adjustable: 600/700/950/1050mA
- The power supply is set to 950mA by default

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	2840-1+5036
WEIGHT IN KG	0.13
POWER CONSUMPTION IN WATTS	24-42

Dimensions

width: 48mm
height: 29mm
length: 152mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	186 - 240 AC/DC
OUTPUT CURRENT IN A	0,6-1,05
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	90
PROTECTION CLASS	II
OUTPUT VOLTAGE	25 - 40 DC
INPUT VOLTAGE SPAN	198 - 264 AC/DC
WARRANTY IN YEARS	3
INPUT VOLTAGE RANGE LUMINAIRE	198 - 264 AC/DC
ETIM GRUPPEN-ID	EC002710
NO DIM FUNCTION	Yes
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany