

PRODUCT NO. 5353-050360

**DOTLUX Construction site floodlight WORKERrocket 70W 5000K CRI>92 IP54 IK07**



to the product page

- Easy to transport thanks to compact design and an ergonomic carrying handle
- High stability thanks to integrated tripod guarantees safe work
- 2 m flexible H07RNF - rubber cable for optimal use on the construction site or outdoors
- Integrated cable holder
- Additional socket IP 54 maximum 1800 Watt / 230 Volt /16A
- Glare-free all-round lighting with 360° beam angle
- Most natural color rendering CRI >92 for demanding users
- Splash-proof housing IP 54

<b>SUCCESSION ARTICLE</b>	5353-150360	<b>BEAM ANGLE</b>	360
<b>WEIGHT IN KG</b>	4.1	<b>PROTECTION CLASS (IP)</b>	IP54
<b>LUMEN PER WATT</b>	86	<b>LIGHT COLOR</b>	white
<b>POWER CONSUMPTION IN WATTS</b>	70	<b>INPUT VOLTAGE</b>	220 - 240 V AC
<b>NET LUMINOUS FLUX IN LUMENS</b>	6000	<b>SERVICE LIFE</b>	approx. 30.000 h at 25°C
		<b>COLOR TEMPERATURE IN KELVIN</b>	5000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 92
		<b>INRUSH CURRENT IN A</b>	0
		<b>IK PROTECTION</b>	IK07
<b>Dimensions</b>		<b>LUMEN PER WATT</b>	86
<b>height:</b> 1352mm		<b>PROTECTION CLASS</b>	I
<b>length:</b> 805mm		<b>HOUSING COLOUR</b>	multicoloured
<b>width:</b> 636mm		<b>WARRANTY IN YEARS</b>	2
		<b>L80/B10</b>	22500
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>MOUNTING LOCATION</b>	Indoor + covered outdoor
		<b>LIFETIME L80/B10 AT 25°C</b>	22500
		<b>LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C</b>	45000
		<b>ETIM GRUPPEN-ID</b>	EC000346
		<b>WITH ILLUMINANT</b>	Yes
		<b>IMPACT STRENGTH</b>	IK07
		<b>SUITABLE FOR LAMP POWER IN W</b>	63.5
		<b>LIFETIME L70/B50 AT 25°C</b>	45000
		<b>LIFETIME L90/B10 AT 25°C</b>	11250
		<b>PULSE DURATION IN µS</b>	0

<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHE</b>	-
<b>LAMP TYPE</b>	Other
<b>CONNECTION TYPE</b>	Other