


PRODUCT NO. 5363-040120

DOTLUX LED panel RIMLESS 620x620x max.42W 1050mA 4000K



to the product page

- Save even more energy with highly efficient LEDs with a luminous efficacy of 165Lm/W
- Frameless design for large-area illumination (also great for SKYLIGHT motifs)
- Homogeneous luminous surface with frosted cover provides pleasant light distribution
- Easy to install and service thanks to DC system plug (Plug&Play compatible with all DOTLUX power supplies)

Power consumption with through-wired power supply Art. 5334

45W @1050 mA = 6950Lm
 42W @ 950 mA = 6490Lm
 30W @ 700 mA = 4800Lm
 26W @ 600 mA = 4120Lm

This product is compatible with our surface mount frame 5226.

SUCCESSION ARTICLE	-	BEAM ANGLE	120
WEIGHT IN KG	1.756	PROTECTION CLASS (IP)	IP40
POWER CONSUMPTION IN WATTS	max. 42	LIGHT COLOR	white
LUMEN PER WATT	max.178	SERVICE LIFE	approx. 50.000 h at 25°C
NET LUMINOUS FLUX IN LUMENS	max. 6950	COLOR TEMPERATURE IN KELVIN	4000
		COLOR-RENDERING-INDEX	CRI > 82
		INRUSH CURRENT IN A	0
		IK protection	
		LUMEN PER WATT	max.178
		PROTECTION CLASS	III
		HOUSING COLOUR	white
		INPUT VOLTAGE SPAN	37-40 DC
		WARRANTY IN YEARS	5
		SUITABLE FOR MOUNTING	Yes
		INPUT VOLTAGE RANGE LUMINAIRE	37-40 DC
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC002892
		MATERIAL COVER	Plastic matt/satinized
		NO DIM FUNCTION	Yes
		COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
		IMPACT STRENGTH	IK02

Dimensions

height: 30mm
length: 620mm
width: 620mm

COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
PULSE DURATION IN μS	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	C
COLOUR OF LIGHT ADJUSTABLE	No