

PRODUCT NO. 3293-240180-B-Ware

DOTLUX LED-Leuchteneinsatz LINEAselect 1437mm 25-75W 4000K dimmbar 1-10V 180° B-Ware



to the product page

- Quick-release fasteners for all connections
- Tool-free mounting rail with integrated through-wiring
- Lamp insert with flexible phase selection and power adjustment
- Optimized transmittance of the diffusing lens
- Self-cooling LED module
- High luminous efficacy thanks to optimized profile design
- Easily replaceable light units with excellent price/performance ratio
- Long life thanks to oversized cooling system
- Suitable for central battery

PREDECESSOR ARTICLE	3293-040180	BEAM ANGLE	180
WEIGHT IN KG	1.7	PROTECTION CLASS (IP)	IP40
LUMEN PER WATT	160	INPUT VOLTAGE	176 - 240 V AC/DC
POWER CONSUMPTION IN WATTS	25-75	SERVICE LIFE	approx. 50.000 h at 25°C
NET LUMINOUS FLUX IN LUMENS	11680	COLOR TEMPERATURE IN KELVIN	4000
		COLOR-RENDERING-INDEX	CRI > 83
		POWER FACTOR	0,98
		LUMEN PER WATT	160
		GLARE-FREE	UGR < 25
Dimensions		SWITCH CYCLES	> 100.000
		WARRANTY IN YEARS	0
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC002892
		DIMMING 1-10 V	Yes