

PRODUCT NO. 3283-040135-B-Ware

DOTLUX LED street light BELUGAmini 73W 4000K SKI without pole mount B-goods



to the product page

- Protection class I with separate overvoltage protection (10,000 V)
- Variety of adapters enables mounting on all pole diameters
- The multilayer lens optics with CREE® LEDs enable uniform light distribution
- Solid cast aluminum housing in RAL 7022 with impact resistance class IK09 and smooth surface
- Highly efficient PHILIPS® LED driver ensures low maintenance costs
- Future-oriented module design with innovative cooling system
- Easy installation and tool-free maintenance
- Integrated pressure equalization valve

PREDECESSOR ARTICLE	3283 2409 2408-1	BEAM ANGLE	135/50
WEIGHT IN KG	5.55	PROTECTION CLASS (IP)	IP66
NET LUMINOUS FLUX IN LUMENS	8760	INPUT VOLTAGE	176 - 240 V AC/DC
POWER CONSUMPTION IN WATTS	max. 73	SERVICE LIFE	approx. 80.000 h at 25°C
LUMEN PER WATT	120	COLOR TEMPERATURE IN KELVIN	4000
		COLOR-RENDERING-INDEX	CRI > 80
		MAST SUPPORT	depending on adapter
		LUMEN PER WATT	120
		PROTECTION CLASS	I
Dimensions		HOUSING COLOUR	gray
		SWITCH CYCLES	> 160.000
		OVERVOLTAGE PROTECTION	up to 10000 V
		INPUT VOLTAGE SPAN	90-264 V AC
		WARRANTY IN YEARS	0
		INPUT VOLTAGE RANGE LUMINAIRE	90-264 V AC
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC000062
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No

DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No