

PRODUCT NO. 600092

DOTLUX LED downlight CIRCLEmini-AC UGR <19 5W 3000K Bundle 5 pcs.



to the product page

- Glare-free luminaire design (UGR>19).
- Perfectly suitable for refurbishments due to the low mounting depth and relatively large aperture
- Easy installation due to the integrated power supply unit and the 15 cm connection cable
- Flexible illumination due to swiveling LED unit
- Set of 5

SUCCESSION ARTICLE	-	BEAM ANGLE	40
WEIGHT IN KG	0.325	PROTECTION CLASS (IP)	IP20
LUMEN PER WATT	80	LIGHT COLOR	white
POWER CONSUMPTION IN WATTS	5	INPUT VOLTAGE	220 - 240 V AC
NET LUMINOUS FLUX IN LUMENS	400	SERVICE LIFE	approx. 20.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000
		COLOR-RENDERING-INDEX	CRi > 82
		POWER FACTOR	0,5
		LUMEN PER WATT	80
		PROTECTION CLASS	II
		HOUSING COLOUR	white
		GLARE-FREE	UGR < 19
		INSTALLATION OPENING DIAMETER IN MM	68-75
		WARRANTY IN YEARS	2
		ASSORTMENT	Ecoline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC001744
		SUITABLE FOR WALL MOUNTING	No
		MATERIAL COVER	Plastic matt/satinized
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
Dimensions			
height:	44mm		
diameter:	85mm		

DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
CONSTANT LIGHT OUTPUT (CLO)	Yes
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	No
EMERGENCY POWER SUPPLY INTEGRATED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	-
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No