

PRODUCT NO. 600093

DOTLUX LED downlight CIRCLEflat 4W 3000K incl. driver Set 5 pieces



to the product page

- Flat design with integrated power supply unit enables use even in difficult installation locations
- Backlight technology with robust aluminum core board and good thermal management
- Wide housing rebate covers inaccurately cut installation opening
- Plastic-coated metal clips ensure a secure hold
- Set of 5

SUCCESSION ARTICLE	-	BEAM ANGLE	120
WEIGHT IN KG	0.25	PROTECTION CLASS (IP)	IP20
LUMEN PER WATT	60	LIGHT COLOR	white
POWER CONSUMPTION IN WATTS	4	INPUT VOLTAGE	220 - 240 V AC
NET LUMINOUS FLUX IN LUMENS	240	SERVICE LIFE	approx. 30.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000
		COLOR-RENDERING-INDEX	CRi > 82
		POWER FACTOR	0,6
		LUMEN PER WATT	60
Dimensions		PROTECTION CLASS	I
height: 26mm		HOUSING COLOUR	white
diameter: 98mm		SWITCH CYCLES	> 60.000
		INSTALLATION OPENING DIAMETER IN MM	77-82
		WARRANTY IN YEARS	2
		ASSORTMENT	Ecoline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC001744
		MATERIAL COVER	Plastic matt/satinized
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No

DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	G
COLOUR OF LIGHT ADJUSTABLE	No