

## **PRODUCT NO. 5389**

## DOTLUX LED rescue light EXIT 3,8W 6000K incl. 4 pictograms 3h operation, (continuous operation or emergency lighting) Li-FEPO4 autom. self test













to the product page

- \"ONE FOR ALL\" One order number for all arrow directions.
- Splash-proof housing (IP65) made of shatterproof polycarbonate
- Replaceable LiFePO4 battery guarantees a light duration of 3 hours
- Different switching programs selectable: continuous or stand-by switching
- Integrated control LED for operating status
- Power consumption in standby mode less than 0.5 Watt
- Automatic self-test function
- Including 4 self-adhesive standard pictograms (left ,right, top, bottom)

SUCCESSION ARTICLE	-	BEAM ANGLE	120
PREDECESSOR ARTICLE	3363, 3009-160180	PROTECTION CLASS (IP)	IP65
		INPUT VOLTAGE	220 - 240 V AC
WEIGHT IN KG	0.61	SERVICE LIFE	approx. 50.000 h at 25°C

POWER CONSUMPTION IN WATTS **OUTPUT LUMEN DURING EMERGENCY** 

**NET LUMINOUS FLUX IN LUMENS** AC 380 / Akku 240 RANGE OF SENSOR **LUMEN PER WATT COLOR TEMPERATURE IN KELVIN** 6000-7000 **COLOR-RENDERING-INDEX** CRI > 70

**POWER FACTOR** 0,45 IK PROTECTION IKO8 Dimensions **BATTERY RUNTIME** 3h **LUMEN PER WATT** 100 length: 349mm PROTECTION CLASS width: 107mm **VOLTAGE TYPE** AC/DC height: 64mm **HOUSING COLOUR** white

**PICTOGRAM INCLUDED** Yes L80/B10 50000

> **ACCORDING TO EU REGULATION** not required 2019/2015

**ENERGY EFFICIENCY CLASS** 

LIFETIME L80/B10 AT 25°C 50000 **LED-LIFETIME LIGHT SOURCE L70/B50** 

100000 AT 25°C EC001957 **ETIM GRUPPEN-ID** WITH ILLUMINANT Yes IKO8

IMPACT STRENGTH **CONSTANT LIGHT OUTPUT (CLO)** Yes



MOUNTING METHOD Deckenanbau

 WITH REMOTE CONTROL
 No

 LIFETIME L70/B50 AT 25°C
 100000

 LIFETIME L90/B10 AT 25°C
 25000

**BEG FUNDING** Only relevant in Germany

ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE

MATERIAL COVER Other