

PRODUCT NO. 600096

DOTLUX LED downlight CIRCLEflat 6W 4000K incl. driver set 5 pieces



to the product page

- Flat design with integrated power supply unit enables use even in difficult installation locations
- Backlight technology in a robust design
- Sturdy mounting clips ensure a secure hold
- Set of 5

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	3022-040120 2823 3022-0FW120
WEIGHT IN KG	0.325
LUMEN PER WATT	65
POWER CONSUMPTION IN WATTS	6
NET LUMINOUS FLUX IN LUMENS	390

Dimensions

height: 26mm
diameter: 118mm

BEAM ANGLE	120
PROTECTION CLASS (IP)	IP20
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 30.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,6
LUMEN PER WATT	65
PROTECTION CLASS	II
HOUSING COLOUR	white
SWITCH CYCLES	> 60.000
INSTALLATION OPENING DIAMETER IN MM	95-100
WARRANTY IN YEARS	2
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GROUP IDENTIFICATION NUMBER	ECC001744
MATERIAL COVER	Plastic matt/satinized
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No

DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
BEG FUNDING	Only relevant in Germany
ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE	G
COLOUR OF LIGHT ADJUSTABLE	No