

PRODUCT NO. 600100

DOTLUX LED recessed panel SQUAREeco IP20 22W 4000K 224x224mm Set 5 pieces



to the product page

- Flat design with integrated power supply unit enables use even in difficult installation locations
- Backlight technology in a robust design
- Sturdy mounting clips ensure a secure hold
- Set of 5

| | |
|------------------------------------|---|
| SUCCESSION ARTICLE | 5095-140120 |
| PREDECESSOR ARTICLE | 1963-1 1963-030120 1963-040120 1963-0FW120 |
| WEIGHT IN KG | 1.1 |
| NET LUMINOUS FLUX IN LUMENS | 1980 |
| POWER CONSUMPTION IN WATTS | 22 |
| LUMEN PER WATT | 90 |

Dimensions

width: 224mm

height: 28mm

length: 224mm

| | |
|---|--------------------------|
| BEAM ANGLE | 120 |
| PROTECTION CLASS (IP) | IP20 |
| LIGHT COLOR | white |
| INPUT VOLTAGE | 220 - 240 V AC |
| SERVICE LIFE | approx. 20.000 h at 25°C |
| COLOR TEMPERATURE IN KELVIN | 4000 |
| COLOR-RENDERING-INDEX | CRI > 82 |
| POWER FACTOR | 0,7 |
| LUMEN PER WATT | 90 |
| PROTECTION CLASS | II |
| VOLTAGE TYPE | AC |
| HOUSING COLOUR | white |
| SWITCH CYCLES | > 40.000 |
| INSTALLATION OPENING WIDTH IN MM | 200 |
| INSTALLATION OPENING DIAMETER IN MM | 190-200 |
| INSTALLATION OPENING LENGHT IN MM | 200 |
| WARRANTY IN YEARS | 2 |
| ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 | not required |
| ETIM GROUP IDENTIFICATION NUMBER | EC001744 |
| MATERIAL COVER | Plastic matt/satinized |
| DIMMING 0-10 V | No |
| DIMMING 1-10 V | No |
| DIMMING DALI | No |

| | |
|--|--------------------------|
| DIMMING DMX | No |
| DIMMING DSI | No |
| DIMMING POTENTIOMETER (INTEGRATED) | No |
| DIMMING LINESWITCH | No |
| DIMMING MANUFACTURER'S PROPRIETARY SYSTEM | No |
| DIMMING MAINS VOLTAGE MODULATION | No |
| DIMMING PHASE CUT-OFF | No |
| DIMMING PROGRAMMABLE | No |
| DIMMING RF | No |
| DIMMING SINE WAVE REDUCTION | No |
| DIMMING TOUCH AND DIM | No |
| DIMMING ZIGBEE | No |
| DIMMING WITH PUSH-BUTTON | No |
| DIMMING DEPENDING ON CONTROL GEAR | No |
| NO DIM FUNCTION | Yes |
| COLOUR CONSISTENCY (MCADAM ELLIPSE) | SDCM6 |
| COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE | No |
| COMPATIBLE WITH APPLE HOMEKIT | No |
| COMPATIBLE WITH GOOGLE ASSISTANT | No |
| COMPATIBLE WITH AMAZON ALEXA | No |
| DIMMING DALI-2 | No |
| DIMMING PHASE CUT-ON | No |
| DIMMING GPRS | No |
| BEG FUNDING | Only relevant in Germany |
| ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE | - |
| COLOUR OF LIGHT ADJUSTABLE | No |