

PRODUCT NO. 3177-160120

DOTLUX LED rescue light EXITmulti, 2W 6000K incl.6 pictograms 3h operation. Li-FEPO4 autom. self test



to the product page

- \"ONE FOR ALL\" One order number for all arrow directions
- Universally mountable escape sign luminaire (2x wall, ceiling installation, rope suspension)
- Replaceable LiFePO4 battery guarantees a light duration of 3 hours
- Different switching programs selectable: continuous or stand-by mode
- Power consumption in standby mode less than 0.5 Watt
- Automatic self-test function with integrated operating status control LED
- Including 6 standard pictograms (left, right, up, down)

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	3177 3177-060120
WEIGHT IN KG	0.94
POWER CONSUMPTION IN WATTS	2
NET LUMINOUS FLUX IN LUMENS	AC 45 / Akku 23
LUMEN PER WATT	22,5

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
RANGE OF SENSOR	30
COLOR TEMPERATURE IN KELVIN	6000-7000
COLOR-RENDERING-INDEX	CRI > 70
POWER FACTOR	0,3
IK PROTECTION	IK08
LUMEN PER WATT	22.5
PROTECTION CLASS	I
VOLTAGE TYPE	AC/DC
HOUSING COLOUR	white
PICTOGRAM INCLUDED	Yes
WARRANTY IN YEARS	3
L80/B10	50000
SELF-TEST	Automatic self-test
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
ETIM GRUPPEN-ID	EC001957
WITH ILLUMINANT	Yes
IMPACT STRENGTH	IK08
MOUNTING METHOD	Wall/ceiling-mounted

Dimensions

length: 350mm
width: 40mm
height: 240mm

LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHE	-
MATERIAL COVER	Other