

PRODUCT NO. 4869-050090-B-Ware

**DOTLUX LED high bay spotlight LIGHTSHOWERclean 150W 5000K DALI dimmable**



to the product page

- optimized light distribution due to glare-reduced lens optics and additional glare control on the housing side
- cooling finless design due to extra large die-cast aluminum housing for perfect thermal management
- suitable for use in food processing plants (HACCP)
- cover made of impact-resistant, shatterproof polycarbonate IK10
- protected against strong water jets and high pressure/steam jet cleaning (IP66/IP69)
- sustainable, repairable product design

<b>SUCCESSION ARTICLE</b>	in Arbeit	<b>BEAM ANGLE</b>	90
<b>WEIGHT IN KG</b>	8.9	<b>PROTECTION CLASS (IP)</b>	other IP66 / IP69
<b>LUMEN PER WATT</b>	140	<b>INPUT VOLTAGE</b>	176 - 240 V AC/DC
<b>POWER CONSUMPTION IN WATTS</b>	150	<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
<b>NET LUMINOUS FLUX IN LUMENS</b>	21000	<b>COLOR TEMPERATURE IN KELVIN</b>	5000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>POWER FACTOR</b>	0,92
		<b>INRUSH CURRENT IN A</b>	0
		<b>IK PROTECTION</b>	IK10
		<b>LUMEN PER WATT</b>	140
		<b>PROTECTION CLASS</b>	I
		<b>HOUSING COLOUR</b>	white
		<b>SWITCH CYCLES</b>	> 100.000
		<b>FOOD-READY</b>	Yes
		<b>OVERVOLTAGE PROTECTION</b>	up to 6000 V
		<b>INPUT VOLTAGE SPAN</b>	100-240 V AC
		<b>WARRANTY IN YEARS</b>	0
		<b>INPUT VOLTAGE RANGE LUMINAIRE</b>	100-240 V AC
		<b>ASSORTMENT</b>	Proline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>ETIM GRUPPEN-ID</b>	EC001744
		<b>DIMMING DALI</b>	Yes
		<b>IMPACT STRENGTH</b>	IK10
		<b>PULSE DURATION IN µS</b>	0
<b>Dimensions</b>			