

PRODUCT NO. 5406

**DOTLUX LED rescue light EXITflat with self-test 3W 6000K incl. 4 pictograms**



to the product page

- For wall mounting with LED light surface on one side
- Replaceable rechargeable battery (LiFePO4) with a lighting duration of 3 hours
- Different switching programs selectable: continuous or standby switching
- Power consumption in standby mode less than 0.5 Watt
- Automatic self-test function with integrated operating status control LED
- Including standard pictograms (left, right, up, down)
- The luminaire has integrated escape route lighting

<b>SUCCESSION ARTICLE</b>	-
<b>PREDECESSOR ARTICLE</b>	3649
<b>WEIGHT IN KG</b>	0.7
<b>POWER CONSUMPTION IN WATTS</b>	3
<b>NET LUMINOUS FLUX IN LUMENS</b>	AC 38 / Akku 29
<b>LUMEN PER WATT</b>	13

**Dimensions**

**length:** 325mm  
**width:** 187mm  
**height:** 31mm

<b>BEAM ANGLE</b>	180
<b>PROTECTION CLASS (IP)</b>	IP20
<b>INPUT VOLTAGE</b>	220 - 240 V AC
<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
<b>RANGE OF SENSOR</b>	30
<b>COLOR TEMPERATURE IN KELVIN</b>	6000
<b>POWER FACTOR</b>	0,5
<b>LUMEN PER WATT</b>	13
<b>PROTECTION CLASS</b>	I
<b>HOUSING COLOUR</b>	multicoloured
<b>INPUT VOLTAGE SPAN</b>	220-240 AC
<b>WARRANTY IN YEARS</b>	3
<b>L80/B10</b>	50000
<b>INPUT VOLTAGE RANGE LUMINAIRE</b>	220-240 AC
<b>ASSORTMENT</b>	Proline
<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
<b>LIFETIME L80/B10 AT 25°C</b>	50000
<b>LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C</b>	100000
<b>ETIM GRUPPEN-ID</b>	EC001957
<b>LIFETIME L70/B50 AT 25°C</b>	100000
<b>LIFETIME L90/B10 AT 25°C</b>	25000
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHE</b>	-
<b>MATERIAL COVER</b>	Other