


PRODUCT NO. 5441-099120

DOTLUX LED luminaire GALAXO Ø400 30W COLORselect and Backlight



to the product page

- Flat, multifunctional luminaire for ceiling, wall and pendant mounting with indirect light component
 - Quick and safe mounting with TWISTLOCK twist lock
 - Switchable, indirect lighting also enables direct surface mounting on wall or ceiling
 - One part number - three light colors adjustable by COLORselect
 - Phase-section dimmable and therefore also compatible with DALI systems with our dimmer Art. 5425
 - High-quality construction due to non-yellowing PMMA light guide technology ensures color-stable light output
 - Suitable for central battery
-
- For use with indirect light, the mounting platform Art. 5445 must be ordered as well
 - For pendant mounting the cable set 5446 and the mounting platform Art. 5445 must be ordered as well
 - The luminaire can be dimmed with the appropriate dimmer 5180 or DALI 5425
 - Highly efficient, BEG eligible luminaire design

WEIGHT IN KG	1.25
POWER CONSUMPTION IN WATTS	30
NET LUMINOUS FLUX IN LUMENS	3600/3900/3780
LUMEN PER WATT	120/130/126

Dimensions

diameter: 397mm
height: 24mm

BEAM ANGLE	120
PROTECTION CLASS (IP)	other Front IP44 / rear IP20
LIGHT COLOR	multicoloured
INPUT VOLTAGE	186 - 240 AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000/4000/5700
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,9
INRUSH CURRENT IN A	0
IK PROTECTION	IK05
LUMEN PER WATT	120/130/126
PROTECTION CLASS	II
VOLTAGE TYPE	AC/DC
HOUSING COLOUR	white
SUITED FOR EMERGENCY LIGHTING	No
SWITCH CYCLES	> 100.000
INSTALLATION OPENING WIDTH IN MM	0
INSTALLATION OPENING DIAMETER IN MM	0
INSTALLATION OPENING LENGTH IN MM	0
WARRANTY IN YEARS	3
L80/B10	50000
RATED CURRENT	0.09
SUITABLE FOR SURFACE MOUNTING	Yes

SUITABLE FOR MOUNTING	No
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
MOUNTING LOCATION	Indoor
LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
ETIM GRUPPEN-ID	EC002892
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	No
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	Yes
SUITABLE FOR LIGHT LINE CONFIGURATION	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	Yes
SUITABLE FOR NUMBER OF LIGHT SOURCES	1
LAMP HOLDER	other Without
MATERIAL COVER	Plastic, structured
TYPE OF CONTROL GEAR	LED operating device current- controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	Yes
DIMMING PHASE CUT-OFF	Yes
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	No
LIGHT DISTRIBUTOR	Diffuser lens/optic/panel
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK05
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	Yes
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No

FILAMENT TEST ACCORDING TO IEC 60695-2-11	650 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	No
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG0
COLOUR OF LIGHT ADJUSTABLE	Positions
LUMINOUS FLUX ADJUSTABLE	Positions
OPERATION BY BLUETOOTH	Yes
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	No
SUITABLE FOR LAMP POWER IN W	30
LAMP TYPE	LED not exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	Yes
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	Yes
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
PULSE DURATION IN µS	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHE	D
SURFACE PROTECTION HOUSING	Untreated
BEAM ANGLE ADJUSTABLE	No
LIGHT SHARING	Symmetric
LIGHT OUTLET	Direct/indirect
TYPE OF GRID	White
BEAM ANGLE	Extreme wide beam >80°