

PRODUCT NO. 4613-B-Ware

DOTLUX BASIS LUNA 490mm B-goods













to the product page

WEIGHT IN KG

POWER CONSUMPTION IN WATTS

NET LUMINOUS FLUX IN LUMENS

0.98 36

max. 3500

Dimensions

height: 40mm diameter: 460mm BEAM ANGLE 160 PROTECTION CLASS (IP) 1P44

 INPUT VOLTAGE
 220 - 240 V AC

 COLOR TEMPERATURE IN KELVIN
 3000/4000/5700

COLOR-RENDERING-INDEXCRI > 82POWER FACTOR0,97INRUSH CURRENT IN A0

SWITCH CYCLES > 100.000

WARRANTY IN YEARS DIMMING 0-10 V No DIMMING 1-10 V No **DIMMING DALI** No DIMMING DMX No DIMMING DSI No **DIMMING POTENTIOMETER** No (INTEGRATED) **DIMMING LINESWITCH** No **DIMMING MANUFACTURER'S** No PROPRIETARY SYSTEM **DIMMING MAINS VOLTAGE** No MODULATION **DIMMING PHASE CUT-OFF** No DIMMING PROGRAMMABLE No **DIMMING RF** No

DIMMING SINE WAVE REDUCTION

DIMMING TOUCH AND DIM

DIMMING ZIGBEE

No

No

No



DIMMING WITH PUSH-BUTTON No DIMMING DEPENDING ON CONTROL No NO DIM FUNCTION Yes DIMMING DALI-2 No DIMMING PHASE CUT-ON No DIMMING GPRS No PULSE DURATION IN µS 0

LIGHT COLOUR ACCORDING TO EN 12464-1

warm white <3300 K

LED-BETRIEBSSTROM IN MA 900