

PRODUCT NO. 2357-440120

DOTLUX LED moisture-proof luminaire MISTRAL IP66 1540mm max.57W 4000K frosted



to the product page

- Faster installation thanks to innovative luminaire design. Combination of LED gear tray and cover.
- Individually replaceable branded components for the lowest maintenance costs
- UV-stable, shatterproof IK08/IP66 polycarbonate housing with frosted cover ensures shadow-free light distribution
- 5-pole through-wired with two internal luminaire connection terminals
- 2 full cable glands & blanking plugs
- Stainless steel fasteners with integrated anti-theft device
- Mounting accessories supplied (chain/ceiling/wall mounting) incl. rear panel punchings
- The D mark of this luminaire with limited surface temperature is a basic requirement for luminaires in locations with a fire hazard (DIN EN 60598-2-24, VDE 0711-2-24) This LED luminaire is suitable for use in food processing plants.
- This means it can also be used in areas that are certified in accordance with the International Featured Standard (IFS) or British Retail Consortium (BRC).
- Sustainable product design thanks to easily replaceable components
- Flicker free
- Adjustable output thanks to Power Select: 65%, 80%, 85%, 100%

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	2357-1 2357-140180 2357-240180 2357-340120
WEIGHT IN KG	2.3
POWER CONSUMPTION IN WATTS	37/46/48/57
NET LUMINOUS FLUX IN LUMENS	5400/6580/6900/7970
LUMEN PER WATT	145/143/143/140

BEAM ANGLE	120
PROTECTION CLASS (IP)	IP66
LIGHT COLOR	white
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,98
INRUSH CURRENT IN A	0
IK PROTECTION	IK08
LUMEN PER WATT	145/143/143/140
PROTECTION CLASS	I
HOUSING COLOUR	gray
SWITCH CYCLES	> 100.000
FOOD-READY	Yes
INPUT VOLTAGE SPAN	176-240
WARRANTY IN YEARS	5
L80/B10	50000
SUITABLE FOR MOUNTING	No
INPUT VOLTAGE RANGE LUMINAIRE	176-240
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required

Dimensions

length: 1540mm
width: 100mm
height: 78mm

LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
ETIM GRUPPEN-ID	EC002892
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	Yes
SUITABLE FOR CEILING MOUNTING	Yes
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	No
MATERIAL COVER	Plastic matt/satinized
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
IMPACT STRENGTH	IK08
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
CONSTANT LIGHT OUTPUT (CLO)	No
TYPE OF WIRING	Through wiring included
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
PULSE DURATION IN µS	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	C
LIGHT OUTLET	Direct
COLOUR OF LIGHT ADJUSTABLE	No

BEAM ANGLE ADJUSTABLE
LIGHT SHARING
BEAM ANGLE

No
Symmetric
Extreme wide beam >80°