

PRODUCT NO. 4944-040160-B-Ware

DOTLUX LED-Lichtbandsystem LINEAcompact 100W breitstrahlend 2886mm 4000K nicht dimmbar B-Ware



to the product page

- New light band concept with 2-length light units for fastest and easiest installation
- All units are delivered fully assembled and only need to be plugged together
- Flexible phase selection directly at the luminaire
- Patent-protected LED cover ensures error-free assembly
- High-quality aluminum core board guarantees perfect cooling and a long service life of the LM80 certified LEDs
- Future-proof with replaceable LED module and separate driver

WEIGHT IN KG	4.633
LUMEN PER WATT	167
POWER CONSUMPTION IN WATTS	100
NET LUMINOUS FLUX IN LUMENS	16700

Dimensions

height: 63mm
length: 2886mm
width: 66mm

BEAM ANGLE	160
PROTECTION CLASS (IP)	IP54
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,98
INRUSH CURRENT IN A	0
LUMEN PER WATT	167
PROTECTION CLASS	I
VOLTAGE TYPE	AC
SWITCH CYCLES	> 100.000
INPUT VOLTAGE SPAN	220-240
WARRANTY IN YEARS	0
INPUT VOLTAGE RANGE LUMINAIRE	220-240
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No

DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0