

PRODUCT NO. 4670-140140

DOTLUX LED damp-proof luminaire SIMPLY IP54 1160mm 51W 4000K IK10



to the product page

- Housing made of shatterproof polycarbonate with frosted cover for shadow-free light distribution
- 3-pole through-wiring with internal luminaire terminal block and two gaskets
- easy-to-maintain modular internal design with highest quality components
- Cable ducts on the back facilitate installation and through-wiring for surface mounting
- Silicone-free
- Sustainable product design due to easily replaceable components

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	4670-040140
WEIGHT IN KG	2.1
LUMEN PER WATT	140
POWER CONSUMPTION IN WATTS	51
NET LUMINOUS FLUX IN LUMENS	7140

BEAM ANGLE	140
PROTECTION CLASS (IP)	IP54
LIGHT COLOR	white
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,95
INRUSH CURRENT IN A	0
IK PROTECTION	IK10
LUMEN PER WATT	140
PROTECTION CLASS	I
HOUSING COLOUR	white
SUITED FOR EMERGENCY LIGHTING	yes
SWITCH CYCLES	> 100.000
WARRANTY IN YEARS	5
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
MATERIAL COVER	Plastic matt/satinized
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No

Dimensions

width: 159mm
height: 85mm
length: 1160mm

DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK10
SUITABLE FOR EMERGENCY LIGHTING	Yes
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	C
COLOUR OF LIGHT ADJUSTABLE	No