

PRODUCT NO. 4773-140050

DOTLUX LED damp-proof luminaire HIGHFORCEnarrow IP66/IP69 1455mm 45W 4000K IK06 2x5pole through-wired DALI including end cap







to the product page

- UV-stable diffuser and housing
- Suitable for outdoor use thanks to integrated pressure compensation valve
- Chemical-resistant special diffuser made of ChemRST material
- Suitable for agricultural applications
- Housing made of impact-resistant polycarbonate
- Impact resistance IKO6
- Suitable for central battery
- IP66/ IP69
- D-certified
- DLG certified
- Distance between both mounting brackets adjustable (700-980mm)
- Mounting brackets allow ceiling and/or wall mounting
- Suitable for mounting heights from 6m thanks to narrow beam optics
- All HIGHFORCE luminaires are delivered without connector plug. Accessories can be found here in the store.

PREDECESSOR ARTICLE4773-040050PROTECTION CLASS (IP)other PR6/ PG9IGHT COLORIGHT COLORMiteWEIGHT IN KG1.8INPUT VOLTAGE767-240 V A/C/CLUMEN PER WATT151GCIOR TEMPERATURE IN KELVIN400POWER CONSUMPTION IN WATS6810COLOR TEMPERATURE IN KELVIN0.812NET LUMINOUS FLUX IN LUMENS6810COLOR-RENDERING-INDEX0.95Inrush CURRENT IN A00.950.01NET LUMINOUS FLUX IN LUMENSKFOODERATURE IN KELVIN10MersonsKFOODERATURE IN KALVIN10Inrush CURRENT IN A00.010.01Inrush CURRENT IN A10100.01Inrush CURRENT IN AFOOD-READY700.01Inrush CURRENT IN SKARRANTY IN YEARS700.01Inrush CURRENT IN YEARSKARGORING TO EN REGULATIONNot requiredInrush CURRENT IN SKCORONING TO EUR REGULATIONNot requiredInrush CURRENT IN AKCORONING TO EUR REGULATION<	SUCCESSION ARTICLE	-	BEAM ANGLE	50
WEIGHT IN KG1.8INPUT VOLTAGE176-240 V AC/DCLUMEN PER WATT151SERVICE LIFEapprox. 50.000 h at 25°CPOWER CONSUMPTION IN WATTS45COLOR TEMPERATURE IN KELVIN4000NET LUMINOUS FLUX IN LUMENS6810COLOR-RENDERING-INDEXCRI > 82POWER FACTOR0.95INRUSH CURRENT IN A0DimensionsKROTECTIONKK06KK06beight: 99mmLUMEN PER WATT151SELength: 1455mmFOOD-READYgrayKR06width: 90mmKASORTMENTVARRANTY IN YEARS7Not requiredKASORTMENTKASORTMENTKiphlineFOOD-READYKASORTMENTKiphlineKiphlineMARRANTY IN YEARS7COLO2892KASORTMENTKASORTMENTKASORTMENTNoNoKASORTMENTNO IM FUNCTIONNoSDCM6	PREDECESSOR ARTICLE	4773-040050	PROTECTION CLASS (IP)	other IP66 / IP69
LUMEN PER WATT151SERVICE LIFEapprox. 50.000 hat 25°CPOWER CONSUMPTION IN WATTS45COLOR TEMPERATURE IN KELVIN4000NET LUMINOUS FLUX IN LUMENS6810COLOR-RENDERING-INDEXCRI > 82POWER FACTOR0.95INRUSH CURRENT IN A0INRUSH CURRENT IN A0IK PROTECTIONIK 06DimensionsLUMEN PER WATT151151Portection CLASSIIIIength: 1455mmFOOD-READYYes161width: 90mmFOOD-READYYes161Iength: 1455mmKARANTY IN YEARS7361Norte CURENTIN SAFOOD-READYHelgline161Iength: 90mmFOOD-READYYes361Iength: 90mmFOODYes361Iength: 90mmFOODYes361Iength: 90mmFOOD <th></th> <th></th> <th>LIGHT COLOR</th> <th>white</th>			LIGHT COLOR	white
POWER CONSUMPTION IN WATTS 45 POWER CONSUMPTION IN WATTS 45 NET LUMINOUS FLUX IN LUMENS 6810 COLOR TEMPERATURE IN KELVIN 4000 COLOR-RENDERING-INDEX CRI > 82 POWER FACTOR INRUSH CURRENT IN A 0 INRUSH CURRENT IN A 0 IK PROTECTION IK PRO	WEIGHT IN KG	1.8	INPUT VOLTAGE	176 - 240 V AC/DC
NET LUMINOUS FLUX IN LUMENS 6810 COLOR-RENDERING-INDEX CRI > 82 POWER FACTOR 0,95 INRUSH CURRENT IN A 0 INRUSH CURRENT IN A 0 Dimensions IK PROTECTION CLASS IK height: 99mm FOOD-READY Yes Length: 1455mm FOOD-READY Yes width: 90mm Kassort IN Years 7 Energy ErfciteNcy CLASS Not required Not required Videnti - 100 mm ENErgy ErfciteNcy CLASS Not required Kordon Factor FOOD-READY Sort MENT Sort Pactor Kordon Factor FOOD-READY Yes Source Width: 90mm Kassort Ment Not Pactor Yes Kordon Factor Kassort Ment Not required Not required Kordon Factor Regulter Not required Not required Not required Kordon Factor Colour Consistency (McAdam) Not Required Not Ment Kordon Factor Colour Consistency (McAdam) Not Ment Not Ment	LUMEN PER WATT	151	SERVICE LIFE	approx. 50.000 h at 25°C
POWER FACTOR0,95INRUSH CURRENT IN A0INRUSH CURRENT IN A0IK PROTECTIONKGGIK DROTECTION151POTECTION CLASS1Iength: 1455mmFOOD-READYVadrath: 90mmVarRANTY IN YEARSVath: 90mmKiphineFOOD-READY9VarRANTY IN YEARS7Interpreting the gradient of the gradient	POWER CONSUMPTION IN WATTS	45	COLOR TEMPERATURE IN KELVIN	4000
IRRUSH CURRENT IN A0IKPROTECTIONIKCGDimensionsIKCGDimensionsLUMEN PER WATTHeight: 99mmIHeight: 99mmHOUSING COLOURHouging COLOURgrayVidth: 90mmYoaVidth: 90mmVARRANTY IN YEARSVidth: 90mmHouging ColourVidth: 90mmHouging ColourVidth: 90mmYoaVidth: 90mmYoa<	NET LUMINOUS FLUX IN LUMENS	6810	COLOR-RENDERING-INDEX	CRI > 82
IK PROTECTIONKGGDimensionsLUMEN PER WATT51height: 99mmPROTECTION CLASSIHousing CoLourgraygrayLength: 1455mmFOOD-READYYeswidth: 90mmWARRANTY IN YEARS7Massort MENTHoglineHoglineKACCORDING TO EU REGULATIONhighlineFUN GRUPPEN-IDEC02892KATERIAL COVERNo TerquiredNo DIM FUNCTIONNoNo DIM FUNCTIONSDCM6			POWER FACTOR	0,95
DimensionsLUMEN PER WATT151PROTECTION CLASSIheight: 99mmHOUSING COLOURgraylength: 1455mmFOOD-READYYeswidth: 90mmWARRANTY IN YEARS7width: 90mmMARRANTY IN YEARS7Kassort MENTHighlineFOOD-READYSoort MENTHighlineFOOD-READYETIM GRUPPEN-IDC002892MATERIAL COVERNo DIM FUNCTIONNoKooling FOLOWERGULATIONNoSocrationationKooling FOLOWERGULATIONSocrationationSocrationationationKooling FOLOWERGULATIONKooling FOLOWERGULATIONNoKooling FOLOWERGULATIONSocrationationationationationationationation			INRUSH CURRENT IN A	0
PROTECTION CLASSIheight: 99mmPROTECTION CLASSIlength: 1455mmHOUSING COLOURgrayvidth: 90mmFOOD-READYYeswidth: 90mmWARRANTY IN YEARS7ASSORTMENTHighlineLENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015not requiredETIM GRUPPEN-IDEC02892MATERIAL COVERPlastic matt/satinizedNo DIM FUNCTIONNoOLIOUR CONSISTENCY (MCADAM BLIPSE)SDCMG			IK PROTECTION	IK06
height: 99mmHOUSING COLOURgraylength: 1455mmFOOD-READYYeswidth: 90mmWARRANTY IN YEARS7ASSORTMENTHighlineLASSORTMENTFOOD-READYNot requiredLASSORTDING TO EU REGULATION 2019/2015Not requiredETIM GRUPPEN-IDEC02892MATERIAL COVERNoNo DIM FUNCTIONNoSDCMGCOLOUR CONSISTENCY (MCADAM) BLIPSE	Dimensions		LUMEN PER WATT	151
Length: 1455mmFOOD-READYYeswidth: 90mmWARRANTY IN YEARS7ASSORTMENTHighlineENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015not requiredETIM GRUPPEN-IDEC02892MATERIAL COVERPlastic matt/satinizedNO DIM FUNCTIONNoOCLOUR CONSISTENCY (MCADAM ELLIPSE)SDCMG			PROTECTION CLASS	I
width: 90mmWARRANTY IN YEARS7ASSORTMENTHighlineKASSORTMENTHighlineENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015not requiredETIM GRUPPEN-IDEC02892MATERIAL COVERPlastic matt/satinizedNO DIM FUNCTIONNoBOLOUR CONSISTENCY (MCADAM) BLLIPSESDCMG	height: 99mm		HOUSING COLOUR	gray
ASSORTMENT Highline ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 Not required 2019/2015 ETIM GRUPPEN-ID ECC02892 MATERIAL COVER Plastic matt/satinized NO DIM FUNCTION No COLOUR CONSISTENCY (MCADAM SDCM6	length: 1455mm		FOOD-READY	Yes
ENERGY EFFICIENCY CLASS not required ACCORDING TO EU REGULATION not required 2019/2015 ETIM GRUPPEN-ID EC002892 MATERIAL COVER Plastic matt/satinized NO DIM FUNCTION No COLOUR CONSISTENCY (MCADAM ELLIPSE) SDCM6	width: 90mm		WARRANTY IN YEARS	7
ACCORDING TO EU REGULATION 2019/2015not requiredETIM GRUPPEN-IDEC002892MATERIAL COVERPlastic matt/satinizedNO DIM FUNCTIONNoCOLOUR CONSISTENCY (MCADAM ELLIPSE)SDCMG			ASSORTMENT	Highline
MATERIAL COVER Plastic matt/satinized NO DIM FUNCTION No COLOUR CONSISTENCY (MCADAM ELLIPSE) SDCM6			ACCORDING TO EU REGULATION	not required
NO DIM FUNCTION No No COLOUR CONSISTENCY (MCADAM SDCMG ELLIPSE)			ETIM GRUPPEN-ID	EC002892
COLOUR CONSISTENCY (MCADAM SDCM6			MATERIAL COVER	Plastic matt/satinized
ELLIPSE)			NO DIM FUNCTION	No
IMPACT STRENGTH IKO6				SDCM6
			IMPACT STRENGTH	IKD6

Page 1/2



COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
DIMMING DALI-2	Yes
PULSE DURATION IN μ S	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	В
COLOUR OF LIGHT ADJUSTABLE	No