

PRODUCT NO. 4782-140120

**DOTLUX LED damp-proof luminaire HIGHFORCEabs IP66/IP69 1455mm 24W 4000K IK06 1x5-pole DALI**



to the product page

- UV-stable diffuser and housing
- Suitable for outdoor use thanks to integrated pressure compensation valve
- Chemical-resistant special diffuser made of ChemRST material
- Suitable for agricultural applications
- Housing made of impact-resistant polycarbonate
- Impact resistance IK06
- Suitable for central battery
- IP66 / IP69
- D-certified
- DLG certified
- Distance between both mounting brackets adjustable (700-980mm)
- Mounting brackets allow ceiling and/or wall mounting
- All HIGHFORCE lights are delivered without connector plug. Accessories can be found here in the store.

<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	120
<b>PREDECESSOR ARTICLE</b>	4782-040120	<b>PROTECTION CLASS (IP)</b>	other IP66 / IP69
<b>WEIGHT IN KG</b>	1.671	<b>LIGHT COLOR</b>	white
<b>POWER CONSUMPTION IN WATTS</b>	24	<b>INPUT VOLTAGE</b>	176 - 240 V AC/DC
<b>NET LUMINOUS FLUX IN LUMENS</b>	3610	<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
<b>LUMEN PER WATT</b>	150	<b>COLOR TEMPERATURE IN KELVIN</b>	4000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>POWER FACTOR</b>	0,95
		<b>INRUSH CURRENT IN A</b>	0
		<b>IK PROTECTION</b>	IK06
		<b>LUMEN PER WATT</b>	150
		<b>PROTECTION CLASS</b>	I
		<b>HOUSING COLOUR</b>	gray
		<b>FOOD-READY</b>	Yes
		<b>WARRANTY IN YEARS</b>	7
		<b>ASSORTMENT</b>	Highline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>ETIM GRUPPEN-ID</b>	EC002892
		<b>MATERIAL COVER</b>	Plastic matt/satinized
		<b>NO DIM FUNCTION</b>	No
		<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
		<b>IMPACT STRENGTH</b>	IK06
<b>Dimensions</b>			
<b>length:</b>	1455mm		
<b>width:</b>	90mm		
<b>height:</b>	99mm		

<b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b>	No
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>DIMMING DALI-2</b>	Yes
<b>PULSE DURATION IN <math>\mu</math>S</b>	0
<b>BEG FUNDING</b>	only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	C
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No