

PRODUCT NO. 5508-060360

DOTLUX LED rescue light EXITflip with CINEMA MODE max.2,5W 6000K incl. 6 pictograms 3h operation, Li-ion battery with self-test



to the product page

- \"ONE FOR ALL\" One order number for all arrow directions
- Replaceable Li-ion battery guarantees a lighting time of 3 hours
- Various switching programs selectable: continuous or standby mode
- Wall/ceiling mounting with infinitely variable folding pictogram
- With the matching track adapter 5519, the EXITflip can be mounted in all 3-phase tracks
- Automatic self-test function with integrated operating status indicator LED
- Power consumption in standby mode less than 0.5 watts
- Power consumption in cinema mode less than 1 watt
- Power consumption in continuous operation less than 2.5 watts
- Includes 6 standard pictograms arrow (left, right, up, down)

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.8	INPUT VOLTAGE	220 - 240 V AC
POWER CONSUMPTION IN WATTS	2,5	SERVICE LIFE	approx. 50.000 h at 25°C
LUMEN PER WATT	7	RANGE OF SENSOR	30
NET LUMINOUS FLUX IN LUMENS	18	COLOR TEMPERATURE IN KELVIN	6000
		COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,3
		LUMEN PER WATT	7
		PROTECTION CLASS	II
Dimensions		HOUSING COLOUR	white
height: 230mm		SUITED FOR EMERGENCY LIGHTING	yes
length: 328mm		L80/B10	50000
width: 43mm		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS	
		ACCORDING TO EU REGULATION	not required
		2019/2015	
		LIFETIME L80/B10 AT 25°C	50000
		ETIM GRUPPEN-ID	EC001957
		SUITABLE FOR EMERGENCY LIGHTING	Yes
		LAMP TYPE	LED
		BEG FUNDING	Only relevant in Germany
		ENERGIEEFFIZIENZKLASSE DER	
		LICHTQUELLE EINER LEUCHE	-
		MATERIAL COVER	Other