

PRODUCT NO. 4965-030120-B-Ware

DOTLUX LED solar wall light FLASHwall with sensor 3.5W 3000K



to the product page

- Solar lithium-ion battery light with motion sensor (2 selectable operating modes).
- Reliable and fast battery charging due to large SOLAR panel, also suitable for indirect light incidence
- Particularly insect-friendly lighting thanks to warm white LEDs and motion sensor
- High-quality, splash-proof aluminium housing with weather-resistant powder coating
- Large homogeneously designed illuminated surface enables glare-free light distribution
- Easy alignment of the luminaire thanks to adjustable stainless steel mounting bracket
- Includes rechargeable battery (replaceable) and mounting accessories

Operating modes Motion sensor:

- A) 15% permanent light intensity after sunset , 100% light intensity in case of movement (duration 15 seconds)
- B) 0% light intensity after sunset, 100% light intensity on movement (duration 15 seconds)

WEIGHT IN KG	1.8	BEAM ANGLE	120
POWER CONSUMPTION IN WATTS	3.5	PROTECTION CLASS (IP)	IP54
NET LUMINOUS FLUX IN LUMENS	250	SERVICE LIFE	approx. 30.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000
		COLOR-RENDERING-INDEX	CRI > 82
		MOTION SENSOR	Infrared, 6-10m, 120°
Dimensions		INRUSH CURRENT IN A	0
length: 160mm		IK PROTECTION	IK06
width: 180mm		BATTERY RUNTIME	3h at 100% / 20h at 15%
height: 255mm		PROTECTION CLASS	III
		HOUSING COLOUR	gray
		WARRANTY IN YEARS	0
		CAPACITIV OF BATTERY IN MAH	1500
		ASSORTMENT	Proline
		ETIM GRUPPEN-ID	EC002892
		IMPACT STRENGTH	IK06
		PULSE DURATION IN µS	0