

PRODUCT NO. 4866-030120

**DOTLUX LED floodlight LENSplus 150W 3000K 120° beam angle**



to the product page

Large variety of different beam angles enables optimum illumination for every situation

- Reliable operation thanks to highly efficient Lumileds® LEDs with 3-step MacAdam binning
- Solid, waterproof, ADC12 die-cast aluminum housing with pressure equalization valve (IP 66/IK08) and high-quality powder coating from Akzo Nobel
- ESG glass \"ULTRA CLEAR\" highly transparent glass for excellent light color and improved light output
- Durable industrial power supply units with 10kV overvoltage protection
- Curved mounting bracket enables easy mounting without having to dismantle the bracket (freely rotatable 320°)
- Incl. 1.5m UV-stable rubber cable (H05RN-F open ends)
- Replaceable components, therefore repairable
- Sustainable product design thanks to easily replaceable components

WEIGHT IN KG	4.5
POWER CONSUMPTION IN WATTS	150
NET LUMINOUS FLUX IN LUMENS	19710
LUMEN PER WATT	131

**Dimensions**

**width:** 320mm  
**height:** 75mm  
**length:** 375mm

BEAM ANGLE	120
PROTECTION CLASS (IP)	IP66
LIGHT COLOR	white
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,98
INRUSH CURRENT IN A	0
IK PROTECTION	IK08
LUMEN PER WATT	131
PROTECTION CLASS	I
VOLTAGE TYPE	AC/DC
HOUSING COLOUR	black
SUITED FOR EMERGENCY LIGHTING	No
SWITCH CYCLES	> 100.000
OVERVOLTAGE PROTECTION	up to 10000 V
INPUT VOLTAGE SPAN	220-240
WARRANTY IN YEARS	7
L80/B10	50000
SUITABLE FOR SURFACE MOUNTING	Yes
SUITABLE FOR MOUNTING	No
DIMMING WITHOUT DIMMER	No
INPUT VOLTAGE RANGE LUMINAIRE	220-240
ASSORTMENT	Highline

<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
<b>LIFETIME L80/B10 AT 25°C</b>	50000
<b>LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C</b>	100000
<b>ETIM GRUPPEN-ID</b>	EC001744
<b>WITH ILLUMINANT</b>	Yes
<b>SUITABLE FOR WALL MOUNTING</b>	Yes
<b>SUITABLE FOR SUSPENDED MOUNTING</b>	No
<b>SUITABLE FOR CEILING MOUNTING</b>	Yes
<b>SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1</b>	No
<b>LAMP HOLDER</b>	-
<b>MATERIAL COVER</b>	Glass transparent
<b>TYPE OF CONTROL GEAR</b>	LED operating device current- controlled
<b>WITH CONTROL GEAR</b>	Yes
<b>DIMMING 0-10 V</b>	No
<b>DIMMING 1-10 V</b>	No
<b>DIMMING DALI</b>	No
<b>DIMMING DMX</b>	No
<b>DIMMING DSI</b>	No
<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	No
<b>LIGHT DISTRIBUTOR</b>	Focal lens
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>IMPACT STRENGTH</b>	IK08
<b>LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24</b>	Yes
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	No
<b>WITH MOVEMENT SENSOR</b>	No
<b>WITH LIGHT SENSOR</b>	No
<b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b>	No
<b>CONSTANT LIGHT OUTPUT (CLO)</b>	No
<b>TYPE OF WIRING</b>	Ending
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No

SUITABLE FOR LOW VOLTAGE CABLE SYSTEM	No
SUITABLE FOR CLAMP-MOUNTING	Yes
SUITABLE FOR LIGHT-TRACK MOUNTING	No
SUITABLE FOR PEDESTAL/FLOOR MOUNTING	Yes
SUITABLE FOR TRAVERSE MOUNTING	Yes
EXCHANGEABLE CONTROL GEAR	No
LAMP TYPE	LED not exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	No
SURFACE BRUSHED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
PULSE DURATION IN µS	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	D
LIGHT OUTLET	Direct
COLOUR OF LIGHT ADJUSTABLE	No
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
LIGHT SHARING	Symmetric
ADJUSTABILITY	Swivelling
SURFACE PROTECTION	Powder coating
BEAM ANGLE	Extreme wide beam >80°
CONNECTION TYPE	Other