

PRODUCT NO. 5448-030115

DOTLUX LED floodlight HLFsport 1600W 3000K dimmable 115°*35° beam angle



to the product page

The compact high-performance floodlight HLFsport is ideal for sports fields and soccer pitches.

- Optimized, asymmetric light control enables glare-free game operation and insect protection ULR<0 with reduced number of floodlights at the same time
- Protection of neighbors from stray light due to special lens geometry
- Corrosion-resistant, powder-coated cast aluminum housing with pressure compensation and high IP/IK protection (IP66/IK08)
- Dali dimmable and therefore compatible with our radio receiver Art. 5007-1 ideal for retrofitting existing installations
- 7 years DOTLUX warranty with an above average lifetime: L80>90.000h
- Very high operational safety with integrated overvoltage protection 20kV
- This luminaire is flicker-free and therefore also suitable for high-definition (HD) television recordings
- Sustainable product design due to easily replaceable components
- Other light colors can be ordered from 1pc onwards
- The floodlight can also be dimmed via DMX. But must be specified when ordering.

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP66
WEIGHT IN KG	32	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	233285	INPUT VOLTAGE	200 - 420V AC
LUMEN PER WATT	145	SERVICE LIFE	approx. ca. 90.000 h at 25° C
POWER CONSUMPTION IN WATTS	1600	COLOR TEMPERATURE IN KELVIN	3000
		COLOR-RENDERING-INDEX	CRI > 70
		POWER FACTOR	0,95
		INRUSH CURRENT IN A	0
		LUMEN PER WATT	145
		PROTECTION CLASS	I
		HOUSING COLOUR	black
		SWITCH CYCLES	>180,000
		OVERVOLTAGE PROTECTION	20000
		INPUT VOLTAGE SPAN	200-420
		WARRANTY IN YEARS	7
		INPUT VOLTAGE RANGE LUMINAIRE	200-420
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		ETIM GRUPPEN-ID	EC001744
		MATERIAL COVER	Glass transparent
		DIMMING DALI	Yes
		NO DIM FUNCTION	No
		COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6

Dimensions	
width: 538mm	
height: 913mm	
length: 756mm	

COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
PULSE DURATION IN μS	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	D
COLOUR OF LIGHT ADJUSTABLE	No