

## **PRODUCT NO.** 3648-040045-B-Ware

## DOTLUX LED-Tracklight EXPLORERgrid 30W 4000K B-Ware











to the product page

- Natural color perception thanks to the extra high CRI value >92
- Easy replacement due to 2.5 m long white connection cable with grounding plug
- High-quality aluminum housing with powder coating white = RAL9003
- Branded ballast from PHILIPS®
- Replaceable high-performance reflectors available as accessories

WEIGHT IN KG 1.376

LUMEN PER WATT 83

POWER CONSUMPTION IN WATTS 30

NET LUMINOUS FLUX IN LUMENS 2500

## Dimensions

height: 174mm length: 240mm width: 80mm BEAM ANGLE 45
PROTECTION CLASS (IP) IP20

**INPUT VOLTAGE** 220 - 240 V AC

**SERVICE LIFE** approx. 50.000 h at 25°C

COLOR TEMPERATURE IN KELVIN 4000
COLOR-RENDERING-INDEX CRI > 92
INRUSH CURRENT IN A 0
LUMEN PER WATT 83
HOUSING COLOUR white
WARRANTY IN YEARS 0
SIMILAR TO RAL-COLOUR 9003
ASSORTMENT Proline

ENERGY EFFICIENCY CLASS

ACCORDING TO EU REGULATION not required

2019/2015

ETIM GRUPPEN-ID EC001744

SUITABLE FOR WALL MOUNTING Yes

PULSE DURATION IN µS 0

DREH- /SCHWENKBAR 355° / 355°

ADJUSTABILITY Rotating and swivelling