


PRODUCT NO. 5370-140090

DOTLUX LED indoor spotlight LIGHTSHOWERsmart Max.200W 4000K Power Select



to the product page

- Glare-reduced hall spotlight thanks to ring lens
- Additional savings potential through optional retrofittable daylight/motion sensors programmable via infrared remote control
- POWERselect in combination with sensors - adjustable directly at the device (50%, 60% 75%, 100%)
- 1-10V dimmable, with optional converter Art.5078 also DALI-capable
- Optimal light output even in high altitudes due to already installed 90° ring lens
- Corrosion protected by powder-coated, robust aluminum housing IP65/IK08
- D-certified for use in fire hazardous locations suitable according to DINEN 60598-2-24, VDE 0711-2-24
- Suitable for use in food processing plants (IFS and BRC)
- Sustainable product design due to easily replaceable components

PREDECESSOR ARTICLE	5370-040090
WEIGHT IN KG	2.7
POWER CONSUMPTION IN WATTS	200
NET LUMINOUS FLUX IN LUMENS	31900

Dimensions

height: 185mm
diameter: 341mm

BEAM ANGLE	90
PROTECTION CLASS (IP)	IP65
LIGHT COLOR	white
INPUT VOLTAGE	220 - 240 V AC
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,9
IK PROTECTION	IK08
PROTECTION CLASS	I
HOUSING COLOUR	black
FOOD-READY	Yes
WARRANTY IN YEARS	5
L80/B10	49500
ENABLED LICENSED PRODUCT	Yes
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	49500
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	99000
ETIM GRUPPEN-ID	EC001744
DIMMING 1-10 V	Yes
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	Yes
DIMMING RF	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6

IMPACT STRENGTH	IK08
LIFETIME L70/B50 AT 25°C	99000
LIFETIME L90/B10 AT 25°C	24750
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHE	B
COLOUR OF LIGHT ADJUSTABLE	No
SERVICE LIFE	ca. 65.000 h bei 25°C