


PRODUCT NO. 4994-199140

DOTLUX Mirror light TREND0sensor 11W 3000/4000/5700K COLORselect



to the product page

- Modern, stylish design with integrated sensor with user-friendly on/off function
 - Maximum illuminated area without visible screw connections
 - EASYbase platform enables quick and easy installation
 - Mounting on existing drill holes possible thanks to free surface on the base plate
 - 2 cable inlets pre-installed (individual inlets can be drilled into the aluminum base if required)
 - Simply set your desired light color yourself, one article number - three light colors through COLORselect
 - Sustainable product design thanks to easily replaceable components
-
- Sensor with on/off function and daylight detection
 - The following values can be set in stages:
 - Reach range (up to 6m)
 - Daylight sensor
 - Light duration

PREDECESSOR ARTICLE	4994-0FW140
WEIGHT IN KG	0.71
POWER CONSUMPTION IN WATTS	11
NET LUMINOUS FLUX IN LUMENS	max. 1200
LUMEN PER WATT	110

Dimensions

length: 600mm
width: 85mm
height: 57mm

BEAM ANGLE	140
PROTECTION CLASS (IP)	IP44
LIGHT COLOR	multicoloured
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000/4000/5700
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,7
INRUSH CURRENT IN A	0
IK PROTECTION	IK08
LUMEN PER WATT	110
PROTECTION CLASS	I
HOUSING COLOUR	multicoloured
SWITCH CYCLES	> 100.000
INPUT VOLTAGE SPAN	220-240
WARRANTY IN YEARS	5
INPUT VOLTAGE RANGE LUMINAIRE	220-240
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
MATERIAL COVER	Plastic matt/satinized
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No

DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
IMPACT STRENGTH	IK08
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
COLOUR OF LIGHT ADJUSTABLE	Positions
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	E